



Dimensions 90 x 19 mm

Operating Frequency Global (860 – 960 MHz)

RF Protocol ISO-18000-6C, EPC Class 1, Gen 2

Chip Impinj Monza R6-P

EPC Memory 96/128 bits

**TID Memory** 48-bit unique serialized TID number

User Memory 64/32 bits

**Common Applications** 

Automotive and Industrial

Asset Tracking Race Timing

Personal ID Badges

| PART NUMBER                                 | RF600721  | RF600727  |
|---|---|---|
| Format                                      | Dry Inlay                                       | Pressure Sensitive Inlay                        |
| Antenna dimensions (CDxMD)                  | 3.543 x 0.748 in (90 x 19 mm)                   | 3.543 x 0.748 in (90 x 19 mm)                   |
| Die-cut dimensions                          | N/A   | 3.67 x 0.87 in (93.175 x 22.175 mm)             |
| Inlay substrate material                    | White PET                                       | White PET                                       |
| Inlay-to-liner adhesive                     | N/A   | S-490 (FASSON)                                  |
| Liner material                              | N/A   | 1.5M Clear PET                                  |
| Face Sheet                                  | N/A   | N/A   |
| Standard pitch                              | 1.25 in (31.8 mm)                               | 1.25 in (31.8 mm)                               |
| Standard web width                          | 3.875 in (98.4 mm)                              | 3.875 in (98.4 mm)                              |
| Total thickness over chip                   | 9-10 mils (229-254 microns)                     | 10-12 mils (254-305 microns)                    |
| Operating temperature                       | -40 to 185F (-40 to 85C)                        | -40 to 185F (-40 to 85C)                        |
| RoHS  | EU Directive 2011/65/EU<br>Compliant            | EU Directive 2011/65/EU<br>Compliant            |
| Quality assurance                           | 100% read tested with-of-tolerance inlay marked | 100% read tested with-of-tolerance inlay marked |
| Un-wind direction                           | Inlay-side Out                                  | Inlay-side Out                                  |
| Core size with adaptor insert               | 3 in (76.2 mm)                                  | 3 in (76.2mm)                                   |
| Maximum roll outer diameter (not to exceed) | 17 in (431.8 mm)                                | 13 in (330.2mm)                                 |
| Average # of units per roll                 | 20,000 verified                                 | 10,000 verified                                 |
| Rev   | 00  | 00  |

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

Warranty: Please refer to Avery Dennison RFID standard terms and conditions.

Product Information: Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

Trademark statement: Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation.