



AR12106CHSSL



Sample photo

Order symbol: AR12106CHSSL
Product nbr: 8561029
Description: PC Enclosure
Remarks: Hinged opaque cover w/S.S. Lockable latch

EAN: 6418074066794
El. number:
Finland:

Including: Hinged cover base with 10-32 brass inserts, latched cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.) Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Dimensions:	Length	Width	Height	Accessories:
mm:	305	254	152	ALBP1210 Aluminum Back Panel
inch:	12.0	10.0	6.0	ADFP1210 Dead Front Panel w/ screws
Materials:				ASP1210 Aluminum Swing Panel
Material:	Polycarbonate			ASPK1210 Swing Panel Kit incl. Panel
Base colour:	RAL 7035 -light grey			ASPHK12 Swing Panel Kit w/o Panel
Cover screws material:	Stainless steel			AMFL10 10" Mounting Flange Set
Cover colour:	RAL 7035 -light grey			
Gasket material:	Polyurethane			
Temperatures:				Rating:
Temperature °C (short term):	-40 ... 140 °C			Ingress Protection (EN 60529): IP68/IP67
Temperature °C (continuous):	-40 ... 80 °C			Impact Resistance (EN 62262): IK07/IK08
Temperature °F (short term):	-40 ... 284 °F			Electrical insulation: Totally insulated
Temperature °F (continuous):	-40 ... 175 °F			Halogen free (DIN/VDE 0472, Part 815): 1
Accessories:				UV resistance: UL 508
ABP1210	Painted Steel Back Panel			Flammability Rating: UL 508
				Glow Wire Test (IEC 695-2-1) °C: 960
				NEMA Class: NEMA 4, 4X, 6, 6P, 12, 13

1.888.238.1155 • Inside USA

 1.205.383.2244 • Outside USA

 info@atlasRFIDstore.com • www.atlasRFIDstore.com

