


MT-120019 MOUNTING KIT FOR FLAT PANEL ANTENNA



CONSTRUCTION

| | |
|--------------------------------|---------------------------|
| INSTALLATION METHOD | To Pole dia 2 3/4" – 3.5" |
| AZIMUTH RANGE: COARSE | ±180° |
| AZIMUTH RANGE: FINE | None |
| TILT RANGE: COARSE | 0° to -10° |
| TILT RANGE: FINE | None |
| AZIMUTH RESOLUTION STEP | None |
| TILT RESOLUTION STEP | None |
| WEIGHT | 2.2 kg |
| PAY LOAD | 20 kg (max) |

MATERIALS

| | |
|------------------|---|
| BRACKETS | Steel, Zinc Plated per QQ-Z-325 type2 class 1 |
| CLAMPS | Steel, Zinc Plated per QQ-Z-325 type2 class 1 |
| FASTENERS | Steel, Zinc Plated per QQ-Z-325 type2 class 1 |

[ADD TO COMPARISON](#) | [COMPARE](#)

ENVIRONMENTAL

| | |
|--|--------------------------|
| TEMPERATURE | -55°C +71°C |
| VIBRATION | IEC 60721-3-4 4M5 Random |
| SHOCK MECHANICAL | IEC 60721-3-4 4M5 |
| HUMIDITY | 0-100% |
| ICE LOADING | 25 mm Radial |
| SALT FOG | IEC 68-2-11 Ka, 500h |
| WIND LOAD (SURVIVAL) | |
| FRONT THRUST | 103.6 kg |
| SIDE THRUST | 8.6 kg |
| INSTALLATION INSTRUCTION DOCUMENT | RD41184700C |

WAIVER!

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

