



RFID

UHF RFID Inlays

AD-227m5

| | |
|----------------------------|-------------------------------------|
| Dimensions | 3.741 x 0.326 in [95.03 x 8.15 mm] |
| Operating Frequency | Global (860 – 960 MHz) |
| RF Protocol | ISO-18000-6C, EPC Class 1, Gen 2 |
| Chip | Imping Monza 5 |
| EPC Memory | 128 bit |
| TID Memory | 48-bit unique serialized TID number |
| USER Memory | 32 bit |

Common Applications

Item Level Retail & Apparel
Supply Chain, Inventory & Logistics
Returnable Transport Units (RTUs)

| PART NUMBER | 600367 600375 [Reverse Wind] | 600366 [Wide Web] | 600368 |
|---|---|---|---|
| Format | Dry Inlay | Dry Inlay | Wet Inlay |
| Antenna dimensions (CD x MD) | 3.741 x 0.326 in [95.03 x 8.15 mm] | 3.741 x 0.326 in [95.03 x 8.15 mm] | 3.741 x 0.326 in [95.03 x 8.15 mm] |
| Die-cut dimensions | N/A | N/A | 3.885 x 0.44 in [98.7 x 11.2 mm] |
| Inlay substrate material | PET | PET | PET |
| Inlay-to-liner adhesive | N/A | N/A | S-490 (FASSON) |
| Liner material | N/A | N/A | 1.5M Clear PET |
| Face Sheet | N/A | N/A | N/A |
| Standard pitch | 0.625 in [15.88 mm] | 0.625 in [15.88 mm] | 0.625 in [15.88 mm] |
| Standard web width | 3.875 in [98.43 mm] | 4.75 in [120.65 mm] | 4.125 in [104.78 mm] |
| Total thickness over chip | 10-13 mils [254-330.2 microns] | 10-13 mils [254-330.2 microns] | 14-17 mils [356-431.8 microns] |
| Operating temperature | -40 to 185 F [-40 to 85 C] | -40 to 185 F [-40 to 85 C] | -40 to 185 F [-40 to 85 C] |
| RoHS | EU Directive 2011/65/EU Compliant | EU Directive 2011/65/EU Compliant | EU Directive 2011/65/EU Compliant |
| Quality assurance | 100% read tested with-of-tolerance inlay marked | 100% read tested with-of-tolerance inlay marked | 100% read tested with-of-tolerance inlay marked |
| Un-wind direction | Inlay-side Out | Inlay-side Out | PS Inlay-side Out |
| Core size with adaptor insert | 6 in [152 mm] | 6 in [152 mm] | 3 in [76 mm] |
| Maximum roll outer diameter (not to exceed) | 12 in [304 mm] | 12 in [304 mm] | 12 in [304 mm] |
| Average # of units per roll | 20,000 good +/- 10% | 20,000 good +/- 10% | 20,000 good +/- 10% |
| Rev | 02 | 02 | 02 |

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

Applications: This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

Warranty: Please refer to Avery Dennison RFID standard terms and conditions.

Product Information: Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

Trademark statement: Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation.