



Powering Business Worldwide

## Eaton 9PXM 4000VA 3600W 208-240V Modular Scalable Online Double-Conversion UPS, Hardwired Input / Output, Cybersecure Network Card Included, 14U, TAA

MODEL NUMBER: 9PXM8S4K



Provides sine wave output, complete battery backup and power protection for mission-critical colocation and edge data centers or other advanced network applications.

### Features

#### Modular, Scalable Battery Backup for Edge Data Centers and Industrial/Commercial Applications

This 9PXM online double-conversion UPS system is superlative power management. Rugged enough to stand up to mission-critical applications, the 9PXM8S4K's compact footprint and N+X redundancy make it a valuable UPS system for colocation and edge data centers, as well as industrial/commercial applications, including retail, financial, government and education. It features hardwired input and output connections.

#### Protects Mission-Critical Equipment against Damage, Downtime and Data Loss

The 9PXM8S4K provides reliable power protection against blackouts, brownouts, surges and line noise that can damage valuable IT equipment or destroy data. It includes a 14U cabinet, one split-phase 4kVA power module, two internal battery modules (per slot) and a NETWORK-M3 Gigabit network card.

#### UPS Has a Power Range up to 12kVA

The UPS cabinet accommodates up to four hot-swappable 4kVA power modules (9PXMSPPM, extras sold separately) total for 12kVA N+X redundancy that eliminates system-level single point of failure. All power modules share the load requirements equally, even if one power module fails or is removed.

#### Expandable Internal Battery Backup Keeps You Operational Through Power Outages

The UPS cabinet requires two hot-swappable extended battery modules (9PXMBAT, extras sold separately) per slot. The valve regulated lead acid (VRLA) battery modules allow you to work through short power failures and give you enough time to safely save files and shut down your system in case of a prolonged blackout. Exclusive ABM® technology increases battery life by 50 percent and closely monitors battery health to provide advanced notice when batteries need replacing.

#### Included Gigabit Network Interface Offers 24/7 Remote Access

The NETWORK-M3 Gigabit network card enables full remote configuration and management, including load shedding, reboots of connected equipment and safe shutdowns. UPS firmware can also be flashed remotely through the NETWORK-M3 without dropping the load, so you don't have to plan for downtime. The card meets both UL 2900-1 and IEC 62443-4-2 standards for cybersecurity, which were developed to address the vulnerability of connected devices to known malware/exploits and to protect business from these risks. The optional Environmental Monitoring Probe Gen 2 (EMPDT1H1C2, sold separately)

### Highlights

- Keeps equipment running during outages to allow time for file saves and safe shutdown
- Exclusive ABM technology with 3-stage charging increases internal battery life by 50%
- Included NETWORK-M3 Gigabit network card enables full remote access and control
- N+X redundancy for power and logic eliminates system-level single point of failure
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Package Includes

- 9PXM8S4K 9PXM 4000VA 3600W 208/240V Online Double-Conversion UPS
- 9PXMSPPM 9PXM split-phase power module
- (2) 9PXMBAT 9PXM internal battery modules
- NETWORK-M2 Gigabit network card
- Owner's manual



Powering Business Worldwide

provides a variety of environmental monitoring capabilities, including temperature and humidity conditions.

**Intuitive Control Panel Keeps You Informed at a Glance**

The UPS control panel includes a graphical LCD, light indicators and function buttons. The control panel provides data and control for the UPS, load status, events, measurements and settings.

**Advanced Communications Ports Allow for Automatic Saves and Shutdowns**

RS-232 and USB ports connect to a serial-enabled or USB-enabled device for a variety of communication options (cables are included). The EPO and ROO connectors permit emergency shutdown or remote restart of all connected equipment. By adding the optional RELAY-MS interface card (sold separately), a dry-contact relay port can be programmed through the LCD to provide reliable communications to automation and industrial components.

**Versatile Installation Options**

You can install the 9PXM8S4K in 14U of space in an EIA-standard 19-inch rack using the optional rackmount kit (9PXM8S4K-RK2, sold separately). Leveling feet and a caster tray are included for secure floor installation.

**TAA-Compliant for GSA Schedule Purchases**

The 9PXM8S4K is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

## Specifications

| OVERVIEW                           |   |
|------------------------------------|---|
| UPC Code                           | 743172091529  |
| UPS Type                           | On-Line   |
| INPUT                              |   |
| Input Phase                        | Single-Phase  |
| Rated input current (Maximum Load) | 125A  |
| Nominal Input Voltage(s) Supported | 110V AC; 120V AC; 127V AC; 208V AC; 220V AC; 240V AC              |
| UPS Input Connection Type          | Hardwire  |
| Maximum Input Amps                 | 125   |
| Input Frequency                    | 50-70 Hz  |
| Input Plug Type                    | Hard-wire   |
| Power Factor (Input)               | 0.99  |
| THDi                               | <5% at nominal input voltage, full load and battery fully charged |
| OUTPUT                             |   |
| Output Capacity (VA)               | 4000  |
| Output Capacity (kVA)              | 4   |
| Output Capacity (Watts)            | 3600  |
| Output Capacity (kW)               | 3.6   |
| Output Capacity Details            | Scalable output capacity from 4kVA to 12kVA                       |



Powering Business Worldwide

|  |  |
|--|--|
| Power Factor                                 | 0.9  |
| Crest Factor                                 | 3:1  |
| Nominal Voltage Details                      | 110V/220V, 120V/208V, 120V/240V, 127V/220V   |
| Frequency Compatibility                      | 50 / 60 Hz   |
| Output Voltage Regulation (Line Mode)        | <5% steady state   |
| Output AC Waveform (AC Mode)                 | Pure Sine wave   |
| Output AC Waveform (Battery Mode)            | Pure Sine wave   |
| Nominal Output Voltage(s) Supported          | 110V; 120V; 127V; 208V; 220V; 240V   |
| Output Receptacles                           | Hardwire   |
| Individually Controllable Load Banks         | No   |
| <b>BATTERY</b>                               |  |
| Battery Type                                 | Valve Regulated Lead Acid (VRLA)   |
| Runtime Full Load (min.)                     | 6 min. (3600W)   |
| Runtime Half Load (min.)                     | 14 min. (1800W)  |
| Expandable Runtime                           | Yes  |
| Expandable Runtime Description               | &nbsp;<a class="productLink" href="//tripplite.eaton.com/Eaton-Internal-Replacement-Battery-for-9PXM-UPS~9PXMBAT">9PXMBAT</a>&nbsp; (2 required per slot). Additional extended runtime options are available. See pg. 8 of the 9PXM brochure under Documents & Downloads for more details. |
| DC System Voltage (VDC)                      | 120 per battery string   |
| Battery Access                               | Battery access door  |
| Internal UPS Replacement Battery Cartridge   | &nbsp;<a class="productLink" href="//tripplite.eaton.com/Eaton-Internal-Replacement-Battery-for-9PXM-UPS~9PXMBAT">9PXMBAT</a>&nbsp;  |
| Battery Replacement Description              | Hot-swappable internal batteries and extended battery modules (EBMs)   |
| Battery Management                           | ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Front Panel LCD Display                      | LCD graphical display  |
| Switches                                     | RPO / ROO  |
| Alarm Cancel Operation                       | Press ESC to silence the alarm   |
| Audible Alarm                                | Audible alarm indicates utility failure, low-battery, overload, other UPS/Battery fault or remote shutdown conditions  |
| LED Indicators                               | 4 status-indicating LEDs   |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| EMI / RFI AC Noise Suppression               | Yes  |
| AC Suppression Response Time                 | 0 ms   |



Powering Business Worldwide

| PHYSICAL  |   |
|---|---|
| Primary Form Factor   | Rackmount; Tower  |
| Rack Height   | 14U   |
| Cooling Method  | Fan   |
| Form Factors Supported  | Rack/Tower  |
| Included Battery Pack Weight (lbs.)                             | 33  |
| Included Battery Pack Weight (kg)                               | 14.97   |
| Installation Form Factors Supported with Included Accessories   | Tower   |
| Maximum Device Depth (cm)                                       | 88.90   |
| Maximum Device Depth (in.)                                      | 35  |
| Maximum Device Depth (mm)                                       | 889   |
| Minimum Required Rack Depth (cm)                                | 96.52   |
| Minimum Required Rack Depth (inches)                            | 38  |
| Minimum Required Rack Depth with External Battery Pack (cm)     | 97  |
| Minimum Required Rack Depth with External Battery Pack (in.)    | 38  |
| Minimum Required Rack Depth without External Battery Pack (cm)  | 97  |
| Minimum Required Rack Depth without External Battery Pack (in.) | 38  |
| Optional Mounting Accessory Notes                               | &nbsp;<a class="productLink" href="//tripplite.eaton.com/eaton-9pxm-standard-rackmount-kit-9PXM2">9PXM2</a>&nbsp;  - Four post rail kit |
| Primary UPS Depth (mm)  | 889   |
| Primary UPS Height (mm)   | 635   |
| Primary UPS Width (mm)  | 445   |
| UPS Power Module Weight (kg)                                    | 10.21   |
| UPS Power Module Weight (lbs.)                                  | 22.5  |
| Unit Dimensions (hwd / in.)                                     | 25.000 x 17.500 x 34.500  |
| Unit Weight (lbs.)  | 229.000   |
| Unit Weight (kg)  | 103.87  |
| ENVIRONMENTAL   |   |
| Operating Temperature Range                                     | 32° to 104°F (0° to 40°C)   |
| Relative Humidity   | 5-95% non-condensing  |
| AC Mode Efficiency Rating (100% Load)                           | 94  |
| AC Economy Mode Efficiency Rating (100% Load)                   | 97  |



Powering Business Worldwide

| COMMUNICATIONS                          |   |
|---|---|
| Network Management Cards                | <a href="https://tripplite.eaton.com/eaton-industrial-gateway-card-mini-slot-for-ups-systems~INDGW-M2">INDGW-M2</a> ; <a href="https://tripplite.eaton.com/eaton-relay-serial-interface-card~RELAY-MS">RELAY-MS</a>   |
| Communications Interface                | RS-232; USB   |
| FEATURES & SPECIFICATIONS               |   |
| High Availability UPS Features          | Hot swappable batteries; Hot swappable UPS power module; Remote management  |
| APPLICATIONS                            |   |
| UPS Applications                        | Mission Critical Applications   |
| STANDARDS & COMPLIANCE                  |   |
| Product Certifications                  | IEC 61000; UL Listed; cUL Listed  |
| Product Compliance                      | FCC (USA); RoHS; Trade Agreements Act (TAA)   |
| WARRANTY & SUPPORT                      |   |
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty   |
| Extended Service Plans                  | <b>ADVANCED DEPOT EXCHANGE</b> Service Part Number: 9SW5Y-11000UC Expedited parts coverage for 5 years Parts, electronics and UPS batteries coverage Next business day shipping Technical support<br><b>5-YEAR ON-SITE PLAN (US ONLY)</b> Service Part Number: WFLN75XX-11000UC On-site parts and labor coverage for years 5 Parts, electronics and UPS batteries coverage 24x7 on-site labor coverage, next-day response Next-day shipping Technical support |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.