

10-Port USB Charging Station with Adjustable Storage, 12V 8A (96W) USB Charger Output

MODEL NUMBER: U280-010-ST



Charges up to 10 electronic devices, including tablets, cell phones and laptops, at the same time via USB connection. Neatly organizes the devices within its adjustable storage brackets while charging.

Description

Whether you're at home or in the office, the U280-010-ST 10-Port USB Charging Station provides plenty of ports and power to keep all your devices at 100% capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to ten tablets, cell phones, laptops and other devices at the same time. It doesn't require a computer, so you can take it anywhere AC power is available.

To charge your USB devices, simply plug the included external dual-voltage (100V–240V) power supply into any NEMA 5-15R outlet, and connect your devices to the available USB ports. The charger protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. A front LED indicates the unit is turned on and receiving AC power.

The U280-010-ST delivers up to 5V 2.4A to each port (5V 1.92A when fully loaded), which is perfect for charging even battery-intensive devices. Plus, adjustable brackets on top of the charger allow it to also act as storage, providing space to neatly organize devices while they charge. You can adjust the brackets to accommodate the number and size of the devices being charged.

Features

Charges Up to 10 Devices at the Same Time Ideal for charging tablets, cell phones, laptops and other devices at home or work
Connect devices to unit's USB ports for proficient charging
Charges anywhere AC power is available—no computer required

Provides Plenty of Juice for Charging Delivers up to 5V, 2.4A per port, enough for charging battery-intensive devices like the Apple iPad*
Protects against overheating, overcurrent and overcharging*
When fully loaded the output per port becomes 5V/1.92A

Also Functions as Efficient Storage Includes 14 adjustable brackets that neatly organize devices while they charge
Brackets are adjustable to accommodate number and size of devices being charged

Easy to Use Included external dual-voltage (100–240V) power supply plugs into any NEMA 5-15R outlet
Front LED indicates when unit is turned on and receiving AC power

Highlights

- Up to 5V, 2.4A per port for charging battery-intensive devices
- External dual-voltage power supply with NEMA 5-15P plug
- Protects against overheating, overcurrent and overcharging
- Includes 14 adjustable storage brackets for organizing devices
- Charges anywhere AC power is available—no computer required

System Requirements

- For international use, the P058-006 (Europe) or P060-006 (UK) power cords can be purchased separately

Package Includes

- 10-Port USB Charging Station
- External Power Supply with C6 Inlet (Input: 100–240V, 50/60 Hz, 2A; Max Output: 12V, 8A, 3 ft.)
- C5 to 5-15P Power Cord
- (14) Storage brackets
- Owner's manual

Specifications



Powering Business Worldwide

TRIPP LITE
SERIES

| OVERVIEW | |
|---|---|
| UPC Code | 037332190352 |
| Product Type | Charging Station |
| Charging Form Factor | Charging Hub |
| Device Compatibility | Phone; Tablet; Amazon Kindle |
| INPUT | |
| AC Power Adapter Plug(s) | NEMA 5-15P North America |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 3A |
| AC Power Adapter Output Specs (V / A) | 12V / 8A |
| AC Power Adapter Cord Length (ft.) | 3 |
| AC Power Adapter Cord Length (m) | 1 |
| OUTPUT | |
| Overload Protection | Yes |
| POWER | |
| Power Source Type | AC Adapter |
| AC Adapter | 100-240V, 50/60Hz, 3A; Output: 12V, 8A, 3-ft. |
| DC Barrel Plug | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve |
| Power Consumption (Watts) | 34 |
| Power Consumption Detail | 34W (Operating) 0.27W (Standby) |
| CONNECTIONS | |
| Number of Ports | 10 |
| Side A - Connector 1 | NEMA 5-15P |
| Side B - Connector 1 | (10) USB A (FEMALE) |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Blue (Power) |
| CHARGING | |
| Number of Charging Ports | 10 |
| Total Charging Amps | 19.2A |
| Total Charging Watts | 96 |
| Charging Method | USB |
| Charging Method Detail | USB-A: 5V/Max 2.4A Apple Fast Charge |



Powering Business Worldwide

TRIPP LITE
SERIES

| | |
|--------------------------------------|---|
| Charging Port Type | (10) USB A (FEMALE) |
| Charging Ports Details | USB-A: Up to 5V/2.4A |
| Charging Ports / Amps | (10) 2.4A |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Polycarbonate |
| Shipping Dimensions (hwd / in.) | 3.11 x 10.59 x 6.14 |
| Shipping Dimensions (hwd / cm) | 7.90 x 26.90 x 15.60 |
| Shipping Weight (lbs.) | 2.71 |
| Shipping Weight (kg) | 1.23 |
| Unit Dimensions (hwd / in.) | 0.984 x 9.370 x 5.276 |
| Unit Dimensions (hwd / cm) | 2,5 x 23,8 x 13,4 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 0.57 |
| Unit Weight (kg) | 0.26 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 41° to 95°F (5° to 35°C) |
| Storage Temperature Range | -4° to 122°F (-20° to 50°C) |
| Relative Humidity | 20% to 80% RH, Non-Condensing |
| FEATURES & SPECIFICATIONS | |
| GaN Technology | No |
| Overcurrent Protection | Yes |
| Overvoltage Protection | Yes |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| IP68 Rated | No |
| IP20 Rated | No |
| STANDARDS & COMPLIANCE | |
| External Power Supply Certifications | CCC; CE; FCC; GS; PSE; RoHS; TUV; UL; cUL |
| Product Certifications | EN 55022; EN 55024 |
| Product Compliance | RoHS; CE (Europe); REACH; FCC Part 15 Class B (USA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |



Powering Business Worldwide

TRIPP LITE
SERIES

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.



atlasRFIDstore

(205) 383-2244

sales@atlasRFIDstore.com

www.atlasRFIDstore.com