

External Battery Pack for SVX Series 3-Phase UPS Systems - Batteries Not Included

MODEL NUMBER: **BP480V370NB**



House user-supplied batteries to extend runtime of a Tripp Lite SVX series UPS.

Features

Add Batteries to Empty Cabinet to Extend the Runtime of SVX Series UPS SystemsBP480V370NB consists of an empty battery cabinet that requires 40 user-supplied 12V 100Ah sealed lead acid batteries (CSB model GPL 121000 or equal). When populated with user-supplied batteries, this external backup battery pack extends runtime for SVX series UPS systems. Up to three external battery pack cabinets may be connected in parallel to increase runtime.

Enjoy Compatibility with SVX Series UPS SystemsThe BP480V370NB external UPS battery pack uses a +/- 240VDC configuration and must be hardwired to a compatible UPS. Circuit breakers provide overcurrent protection. The BP480V370NB is compatible with UPS models that begin with SVX30, SVX60, SVX90, SVX120, SVX150, SVX180 and SVX210.

Maintain a Uniform Look in Network EnvironmentsMade of powder-coated steel, the battery cabinet is designed to match the SVX series UPS systems to keep a consistent look in your server room or data center. The cabinet door is lockable to control access to batteries. The top of the cabinet has knockouts for user-supplied power output cables. Front and rear vents allow the free flow of warm air out of the cabinet.

One-Year WarrantyThe BP480V370NB is backed by a one-year limited warranty, ensuring reliability and performance.

Specifications

OVERVIEW	
UPC Code	037332225269
INPUT	
Input Phase	3-Phase

Highlights

- Extends runtime of SVX series UPS systems using a +/- 240VDC configuration
- Requires 40 user-supplied 12V 100Ah sealed lead acid batteries
- Requires hardwire installation; circuit breakers provide overcurrent protection
- Up to 3 battery pack cabinets may be connected in parallel to increase runtime

Applications

- House external battery backup pack for an SVX series 3-phase UPS system
- Provide extended battery runtime for an SVX series 3-phase UPS system

System Requirements

- Compatible SVX Series UPS System
- 40 user-supplied 12V 100Ah sealed lead acid batteries (CSB model GPL 121000 or equal)

Package Includes

- BP480V370NB External Battery Pack (No Batteries)
- Owner's manual



Powering Business Worldwide



BATTERY	
Expandable Runtime	Yes
DC System Voltage (VDC)	+/- 240VDC
UPS Connection	Hardwire (contractor supplies wiring - see Owner's Manual for requirements and installation information)
PHYSICAL	
Material of Construction	Steel
Rack Height	0U
External Battery Pack Form Factor	Tower
Installation Form Factors Supported with Included Accessories	Tower
Shipping Dimensions (hwd / in.)	80.31 x 28.74 x 48.00
Shipping Weight (kg)	319.78
Unit Dimensions (hwd / in.)	78.940 x 25.470 x 43.300
Unit Dimensions (hwd / cm)	200,5 x 64,7 x 110,0
Unit Weight (lbs.)	266
Unit Weight (kg)	120.66
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.