

## 72V Extended Battery Module (EBM) for 1950VA and 3000VA SmartPro UPS Systems, 2U Rack/Tower

MODEL NUMBER: **BP72VRM2U**



External battery pack provides extended runtime for compatible UPS systems in small business, education, retail, financial or healthcare applications.

### Features

#### Backup Battery Module Gives Your Compatible Eaton UPS System Extended Runtime

The BP72VRM2U offers extended battery runtime when used in conjunction with the 2023 refreshed 1950VA and 3000VA SmartPro® UPS systems. It can also be daisy-chained for a maximum of four matching battery packs to deliver even longer extended-run operations. Heavy-gauge cabling with high-current DC connectors is included for safe, simple installation.

#### Supports 2U Rack or Tower Installation

This backup battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch open frame racks or enclosures using the included 4-post rail kit and mounting brackets. Tower stands are also included for optional upright configuration.

### Highlights

- Connects to select expandable UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Includes heavy-gauge cabling with high-current 72V DC connectors
- Supports 2U rack mounting or upright tower installation using included accessories

### System Requirements

Compatible only with 2023 refreshed SMART2200RMXL2U, SMART2200RMXLN, SMART3000RMXL2U, SMART3000RMXLN, SMX3000XLRT2UA, and SMX3000XLRT2UN SmartPro UPS systems

### Package Includes

- BP72VRM2U External 72V Battery Pack
- External battery cable
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

## Specifications

| OVERVIEW                                   |                                                                                                             |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| UPC Code                                   | 037332279101                                                                                                |
| INPUT                                      |                                                                                                             |
| Input Phase                                | Single-Phase                                                                                                |
| BATTERY                                    |                                                                                                             |
| Battery Type                               | Valve Regulated Lead Acid (VRLA)                                                                            |
| DC System Voltage (VDC)                    | 72                                                                                                          |
| Internal UPS Replacement Battery Cartridge | <a href="https://tripplite.eaton.com/replacement-battery-for-eaton-9px-ups-and-ebm-744-A3121">744-A3121</a> |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                               |                                                                                                      |
|---------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| Battery Replacement Description                               | Hot-swappable, user-replaceable batteries. EBM requires 2x 744-A3121 Replacement Battery Cartridges. |
| <b>PHYSICAL</b>                                               |                                                                                                      |
| Rack Height                                                   | 2U                                                                                                   |
| External Battery Pack Form Factor                             | Rack/Tower                                                                                           |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount; Tower                                                                      |
| Minimum Required Rack Depth (cm)                              | 68.58                                                                                                |
| Minimum Required Rack Depth (inches)                          | 27                                                                                                   |
| Unit Dimensions (hwd / in.)                                   | 3.400 x 17.200 x 23.700                                                                              |
| Unit Weight (lbs.)                                            | 89.1                                                                                                 |
| Unit Weight (kg)                                              | 40.42                                                                                                |
| <b>STANDARDS &amp; COMPLIANCE</b>                             |                                                                                                      |
| Product Certifications                                        | CAN/CSA C22.2; cTUVus; cUL Listed                                                                    |
| Product Compliance                                            | CE (Europe); RoHS                                                                                    |
| <b>WARRANTY &amp; SUPPORT</b>                                 |                                                                                                      |
| Product Warranty Period (U.S. & Canada)                       | 2-year limited warranty                                                                              |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.