

## 72V Extended Battery Module (EBM) for Select 2200VA and 3000VA SmartPro UPS Systems, 2U Rack/Tower

MODEL NUMBER: **BP72VRXLTA**



External battery pack provides extended runtime for compatible UPS systems in government, military, education, retail, financial or healthcare applications.

### Features

#### Backup Battery Module Gives Your Compatible UPS System Extended Runtime

The BP72VRXLTA offers extended battery runtime when used in conjunction with certain Eaton Tripp Lite series 2200VA and 3000VA SmartPro® UPS systems, such as the SMART2200RXLTA and SMART3000RXLTA. It can also be daisy-chained for a maximum of four matching battery packs to deliver even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for safe, simple installation.

#### Equipped with External Battery Auto-Detect

The automatic battery detection feature works with the connected UPS system to detect the EBM and automatically update runtimes.

#### Versatile Design Supports 2U Rack or Tower Installation

This VRLA battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch open frame racks or enclosures using the included 4-post rail kit and mounting brackets. Tower stands are also included for optional upright configuration.

### Highlights

- Connects to SMART2200RXLTA and SMART3000RXLTA UPS systems to provide additional runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Auto-detect feature lets compatible UPS systems automatically update runtime
- Versatile design allows for 2U rack mounting or upright tower configuration

### System Requirements

Compatible only with Eaton Tripp Lite series SMART2200RXLTA and SMART3000RXLTA SmartPro UPS systems

### Package Includes

- BP72VRXLTA 72V Extended Battery Module
- External battery cable
- Auto-detection cable
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

## Specifications

OVERVIEW	
UPC Code	786689816049
INPUT	
Input Phase	Single-Phase
BATTERY	



Powering Business Worldwide

TRIPP LITE  
SERIES

Battery Type	Valve Regulated Lead Acid (VRLA)
DC System Voltage (VDC)	72
Internal UPS Replacement Battery Cartridge	&nbsp;<a class="productLink" href="//tripplite.eaton.com/replacement-battery-for-eaton-9px-ups-and-ebm~744-A3121">744-A3121</a>&nbsp;
Battery Replacement Description	Hot-swappable, user-replaceable batteries. EBM requires 2x 744-A3121 Replacement Battery Cartridges.
UPS Connection	Detachable power and data cables with series specific connectors.
Typical Battery Lifespan	3 to 5 Years
<b>PHYSICAL</b>	
Material of Construction	Steel
Rack Height	2U
External Battery Pack Form Factor	Rack/Tower
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount; Tower
Minimum Required Rack Depth (cm)	63.50
Minimum Required Rack Depth (inches)	25
Unit Dimensions (hwd / in.)	3.400 x 17.200 x 23.700
Unit Weight (lbs.)	89.1
Unit Weight (kg)	40.42
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA C22.2; cTUVus
Product Compliance	CE (Europe); RoHS; UKCA; WEEE
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (U.S. & Canada)	2-year warranty, 3 year with registration. Note:&nbsp;<a class="insuranceLink" href="//tripplite.eaton.com/support/product-warranty-registration">Registration is required</a>&nbsp;for 3-year warranty.

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.