






Powering Business Worldwide

## 3-Phase Managed Rack PDU G4, 120/208V, 42 Outlets, 24A, 8.6kW, L21-30 Input, 10 ft. Cord, 0U Vertical

MODEL NUMBER: **EVMA2130X**



Managed PDU with enhanced cybersecurity and global approval is ideal for data center managers seeking to streamline PDU procurement and management.

### Features

#### Three-Phase Managed PDU Ideal for Data Center Managers with Large-Scale Distributed IT

The EVMA2130X Rack PDU G4 is ideal for streamlining PDU procurement and deployment within a 42U rack in an enterprise data center, colocation data center or distributed IT infrastructure. Equipped to meet even the most diverse data center rack power needs, the EVMA2130X delivers versatile, enterprise-quality power distribution.

#### Market-Leading Cybersecurity Ensures Your Data Is Kept Safe

Chain-of-trust encryption and secure firmware boot capability prevent the EVMA2130X PDU from being a cyberattack vulnerability point on a network. An embedded, hot-swappable gigabit network module (GNM) offers enhanced management and cybersecurity, including zero-trust architecture and zero-touch provisioning. The EVMA2130X is compatible with select Eaton Brightlayer Data Centers suite software solutions that enable extensive automation and remote management to shorten response times to power issues and ensure timely updates for stronger cybersecurity.

#### Remote Management Saves Time and Money

The GNM with multi-color screen supports performance management software for real-time reports, trend charts, dashboards and alerts that are prioritized by severity, as well as remote troubleshooting and automated responses during power events. The EVMA2130X is compatible with optional environmental sensors (sold separately) that provide alerts about temperature, humidity and dry-contact device connections.

#### 42 Outlets Give You Plenty of Power Options

The EVMA2130X features 24 C13 outlets, which accept C14 connectors, and 18 high-retention C39 combo outlets, which accept both C14 and C20 connectors, adding flexibility to deployments and reducing the quantity of PDUs you will need to purchase and install.

#### Outlet-Level Control Boosts Performance and Efficiency

All 42 outlets provide metering, monitoring and switching for granular power data and precision control of power delivery. The outlets are evenly distributed into six color-coded load banks to improve load balancing and organize connections in a crowded rack.

#### Convenient Box-to-Rack Installation

### Highlights

- Embedded gigabit network module offers market-leading cybersecurity
- 42 outlets include 24 C13 and 18 universal C39, which accepts C14 and C20 plugs; Compatible with Eaton Tripp Lite P-Lock Power Cords
- Power metering, monitoring and switching available at the outlet level
- Toolless mounting buttons allow 0U vertical installation in your 42U rack

### Package Includes

EVMA2130X 3-Phase Managed Rack PDU G4



Powering Business Worldwide

This EVMA2130X rack PDU (rPDU) features toolless mounting buttons that allow front- or side-facing rack installation, depending on your rack's layout and your power needs. The 10-foot power cord with L21-30 input connects to a compatible AC source. Low-profile circuit breakers are flush with the lightweight aluminum chassis, and the narrow two-inch width saves space within the rack for revenue-generating equipment. You can cascade up to 40 EVMA2130X models with each model maintaining its own individual IP address from a single network connection point.

## Specifications

| OVERVIEW                            |                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------|
| UPC Code                            | 786689787660                                                                          |
| PDU Type                            | Managed                                                                               |
| INPUT                               |                                                                                       |
| Input Phase                         | 3-Phase                                                                               |
| PDU Input Voltage                   | 120/208V                                                                              |
| Nominal Input Voltage Description   | 3P: 120/208V                                                                          |
| Recommended Electrical Service      | Three-phase 120/208V service                                                          |
| Maximum Input Amps                  | 30                                                                                    |
| Input Connection Type               | NEMA L21-30P                                                                          |
| PDU Plug Type                       | NEMA L21-30P                                                                          |
| Voltage Compatibility (VAC)         | 208; 3-Phase                                                                          |
| Input Plug Type                     | NEMA L21-30P                                                                          |
| Input Cord Details                  | NEMA L21-30P                                                                          |
| Input Cord Length (ft.)             | 10                                                                                    |
| Input Cord Length (m)               | 3.05                                                                                  |
| OUTPUT                              |                                                                                       |
| Output Capacity (kVA)               | 8.6                                                                                   |
| Output Capacity (Watts)             | 8600                                                                                  |
| Output Capacity (kW)                | 8.6                                                                                   |
| Output Capacity Details             | 8.6kW (120-208V) total capacity; 24A max per output phase                             |
| Frequency Compatibility             | 50 / 60 Hz                                                                            |
| Output Receptacle Details           | C39 Compatible with P-Lock Power Cords                                                |
| Output Circuit Breakers             | (3) low-profile circuit breakers. 20A (US). One circuit breaker per two outlet banks. |
| Nominal Output Voltage(s) Supported | 120V; 208V                                                                            |
| Output Receptacles                  | (24) C13; (18) C39                                                                    |
| Overload Protection                 | (3) 2-pole 20A circuit breakers                                                       |



Powering Business Worldwide

| CONNECTIONS                          |                                                                                                                                                                                               |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethernet Interface                   | Yes                                                                                                                                                                                           |
| Serial Interface                     | Yes                                                                                                                                                                                           |
| Daisy-chainable / Cascadable         | Yes                                                                                                                                                                                           |
| Daisy-chainable / Cascadable Details | Cascade up to 40 PDUs                                                                                                                                                                         |
| USER INTERFACE, ALERTS & CONTROLS    |                                                                                                                                                                                               |
| Front Panel LCD Display              | LCD pixel display with outlet-level readings and automatic shut-off to save energy. Set IP address, rotate display, control outlets, view alarms and read current, voltage, power and energy. |
| LED Indicators                       | Green = outlet is on Red = PDU has power but outlet is off                                                                                                                                    |
| Current Measurement Accuracy (Amps)  | +/-1%                                                                                                                                                                                         |
| Voltage Measurement Accuracy (Volts) | +/-1%                                                                                                                                                                                         |
| Power Measurement Accuracy (Watts)   | +/-1%                                                                                                                                                                                         |
| SURGE / NOISE SUPPRESSION            |                                                                                                                                                                                               |
| Automatic Shut-Off                   | No                                                                                                                                                                                            |
| PHYSICAL                             |                                                                                                                                                                                               |
| Material of Construction             | Aluminum                                                                                                                                                                                      |
| Rack Height                          | 0U                                                                                                                                                                                            |
| Form Factors Supported               | Vertical                                                                                                                                                                                      |
| Housing Color                        | Black                                                                                                                                                                                         |
| PDU Form Factor                      | Vertical (0U)                                                                                                                                                                                 |
| Shipping Dimensions (hwd / in.)      | 75.00 x 7.72 x 5.40                                                                                                                                                                           |
| Shipping Dimensions (hwd / cm)       | 190.50 x 19.61 x 13.72                                                                                                                                                                        |
| Shipping Weight (lbs.)               | 21.60                                                                                                                                                                                         |
| Shipping Weight (kg)                 | 9.80                                                                                                                                                                                          |
| Unit Dimensions (hwd / in.)          | 68.100 x 2.000 x 2.080                                                                                                                                                                        |
| Unit Dimensions (hwd / cm)           | 172.97 x 5.08 x 5.28                                                                                                                                                                          |
| Unit Weight (lbs.)                   | 19.4                                                                                                                                                                                          |
| Unit Weight (kg)                     | 8.80                                                                                                                                                                                          |
| Mounting Details                     | Factory-installed shoulder-style aluminum mounting buttons. 61.25" center-to-center Alternative flush-style mounting buttons also included with PDU                                           |
| ENVIRONMENTAL                        |                                                                                                                                                                                               |
| Operating Temperature Range          | 32° to 140°F (0° to 60°C)                                                                                                                                                                     |



Powering Business Worldwide

|                                         |                                                                                |
|-----------------------------------------|--------------------------------------------------------------------------------|
| Storage Temperature Range               | -13° to 149°F (-25° to 65°C)                                                   |
| Relative Humidity                       | 5% to 95% non-condensing                                                       |
| Operating Elevation                     | 0-10000 ft. (0-3000 m)                                                         |
| Storage Elevation (ft.)                 | 0-50000 ft. (0-15240 m)                                                        |
| <b>COMMUNICATIONS</b>                   |                                                                                |
| Network Monitoring Port                 | Serial/Ethernet ports for environmental monitoring and daisy-chain connections |
| SNMP Compatibility                      | Yes                                                                            |
| Network Compatibility                   | 10 Mbps; 100 Mbps (Fast Ethernet); 1 Gbps (Gigabit); 1000 Mbps                 |
| Network Speed Details                   | 10 Mbps; 100 Mbps (Fast Ethernet); 1 Gbps (Gigabit); 1000 Mbps                 |
| Network Management Card Description     | Eaton Gigabit Network Module G4                                                |
| <b>FEATURES &amp; SPECIFICATIONS</b>    |                                                                                |
| High Availability PDU Features          | Advanced cybersecurity; Remote management of individual outlets                |
| <b>STANDARDS &amp; COMPLIANCE</b>       |                                                                                |
| Product Certifications                  | ICES (Canada); UL 62368-1; cTUVus                                              |
| Product Compliance                      | FCC Part 15 Class A (USA); RoHS                                                |
| <b>WARRANTY &amp; SUPPORT</b>           |                                                                                |
| Product Warranty Period (Worldwide)     | 3-year limited warranty                                                        |
| Product Warranty Period (U.S. & Canada) | 3-year limited warranty                                                        |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.