

# PDU Power Cord, C13 to C14 - 13A, 250V, 16 AWG, 5 ft. (1.52 m), Black

MODEL NUMBER: P004-005-13A



Computer power extension cord connects 2 devices with C13/C14 power connectors or extends your existing power connection by 5 ft.

## Features

**C14-to-C13 Power Cable Connects Computers, Printers, Servers and Other Equipment** This IEC-320-C14 to IEC-320-C13 cable is designed for small data center, office workstation and other lower-amp applications. This C14 male to C13 female cord can be used to power a computer, server or monitor; attach a server or drive to a UPS system or PDU; or extend an existing connection up to five feet. The five-foot length allows you flexibility in placing equipment with respect to the power outlet.

## Highlights

- Recommended for powering computers, printers and other essential peripherals
- Adds 5 ft. to your existing power connection to provide flexibility in placing devices
- C13-to-C14 PDU-style extension cord is ideal replacement for worn-out or missing cable

## Applications

- Connect devices like computers, servers and monitors to a PDU up to 5 ft. away in your data center
- Extend an existing power connection up to 5 ft. to more easily place a device or reach a power source near your workstation
- Provide a high-quality replacement for a worn-out or missing power cord

## Package Includes

- P004-005-13A C14 Male to C13 Female Power Cable, 5 ft., Black

## Specifications

| OVERVIEW                    |   |
|-----------------------------|---|
| UPC Code                    | 037332180469                                      |
| Product Type                | PDU Extension Power Cord                          |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region              | Global  |
| INPUT                       |   |
| Maximum Input Amps          | 13  |
| Voltage Compatibility (VAC) | 250   |
| CONNECTIONS                 |   |
| Side A - Connector 1        | IEC-320-C14                                       |
| Side B - Connector 1        | IEC-320-C13                                       |
| Connector Style             | Straight  |



Powering Business Worldwide

TRIPP LITE  
SERIES

| PHYSICAL                           |                             |
|------------------------------------|-----------------------------|
| Color                              | Black                       |
| Plug Color                         | Black                       |
| Cable Jacket Color                 | Black                       |
| Connector Color                    | Black                       |
| Cable Jacket Material              | PVC                         |
| Cable Jacket Rating                | FT2                         |
| Power Cord Jacket Type             | SJT                         |
| Cable Outer Diameter (OD)          | 9mm                         |
| Number of Conductors               | 3                           |
| Wire Gauge (AWG)                   | 16                          |
| Wire Gauge (OD - mm <sup>2</sup> ) | 1.31                        |
| Power Cord Color                   | Black                       |
| Cable Length (ft.)                 | 5                           |
| Cable Length (m)                   | 1.52                        |
| Shipping Dimensions (hwd / in.)    | 10.00 x 7.10 x 0.10         |
| Shipping Dimensions (hwd / cm)     | 25.40 x 18.03 x 0.25        |
| Shipping Weight (lbs.)             | 0.46                        |
| Shipping Weight (kg)               | 0.21                        |
| ENVIRONMENTAL                      |                             |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range           | 20% to 80% RH               |
| Storage Humidity Range             | 20% to 80% RH               |
| FEATURES & SPECIFICATIONS          |                             |
| Antibacterial                      | No                          |
| Angled Plug                        | No                          |
| High Voltage                       | Yes                         |
| Locking Plug                       | No                          |
| Coiled Power Cord                  | No                          |
| Locking Power Cord                 | No                          |
| Locking                            | No                          |
| STANDARDS & COMPLIANCE             |                             |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| Product Certifications              | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance                  | RoHS; REACH                         |
| <b>WARRANTY &amp; SUPPORT</b>       |                                     |
| Product Warranty Period (Worldwide) | Lifetime limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.