

## Power Cord Adapter, C14 to C5 - 7A, 125V, Black

MODEL NUMBER: P014-000



C14 to C5 adapter connects your notebook or laptop with a 3-slot C6 power connector to a C13 outlet on a surge protector or UPS.

### Features

**IEC C14 to IEC C5 Adapter Connects Notebook Computers to an AC Outlet** This UL-listed C14 to C5 power cord adapter converts a C6 plug into a C14 connector and is ideal for a device's built-in power cord that doesn't match an available outlet. You can use this adapter to connect a notebook computer, laptop or other device with a three-slot C6 power cord to a surge protector or UPS system with a C13 outlet.

## Specifications

| OVERVIEW                    |                            |
|-----------------------------|----------------------------|
| UPC Code                    | 037332218001               |
| Device Compatibility        | Laptop; Computer; UPS; PDU |
| Country/Region              | North America              |
| INPUT                       |                            |
| Maximum Input Amps          | 7                          |
| Voltage Compatibility (VAC) | 125                        |
| CONNECTIONS                 |                            |
| Side A - Connector 1        | IEC-320-C14                |
| Side B - Connector 1        | IEC-320-C5                 |
| PHYSICAL                    |                            |
| Plug Color                  | Black                      |
| Cable Jacket Color          | Black                      |

### Highlights

- Recommended for powering notebook computers and laptops with C6 inlets
- Converts a C6 connector into a C14 connector to match an available outlet

### Applications

- Connect a laptop or notebook computer to a C13 outlet near your workstation
- Connect a laptop or notebook to a surge protector at a trade show or lecture hall

### Package Includes

- P014-000 IEC C14 to IEC C5 Power Cord Adapter, Black



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Wire Gauge (AWG)                     | N/A                                 |
| Wire Gauge (OD - mm <sup>2</sup> )   | N/A                                 |
| Cable Length (ft.)                   | 0                                   |
| Cable Length (m)                     | 0.00                                |
| Shipping Dimensions (hwd / in.)      | 5.00 x 3.98 x 0.50                  |
| Shipping Dimensions (hwd / cm)       | 12.70 x 10.11 x 1.27                |
| Shipping Weight (lbs.)               | 0.07                                |
| Shipping Weight (kg)                 | 0.03                                |
| Unit Dimensions (hwd / in.)          | 2.550 x 1.140 x 0.820               |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 14° to 140°F (-10° to 60°C)         |
| Storage Temperature Range            | 14° to 140°F (-10° to 60°C)         |
| Operating Humidity Range             | 30% to 80% RH                       |
| Storage Humidity Range               | 30% to 80% RH                       |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| Antibacterial                        | No                                  |
| Angled Plug                          | No                                  |
| High Voltage                         | No                                  |
| Locking Plug                         | No                                  |
| Coiled Power Cord                    | No                                  |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Certifications               | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance                   | RoHS                                |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.