

## 4-Outlet Vertical Power Strip, 2-15A & 2-20A, 120V, 15 ft. (4.57 m) Cord, 5-20P, 12 in.

MODEL NUMBER: PS120420



The P120420 power strip provides horizontal or vertical power distribution for rackmount, raceway and workbench applications in a convenient 12-in. mountable housing.

### Description

The PS120420 provides a 20-amp, 120v power strip with 2 standard NEMA 5-15 outlets and 2 NEMA 5-20R outlets in a rugged, all-metal, mountable housing. It allows for both vertical and horizontal mounting, making it ideal for a variety of uses including office, rackmount, workbench, industrial and telecom applications. With a NEMA 5-20P, 15-ft. (4.57 m) power cord, you don't have to install the PS120420 next to outlets you already have; it can be mounted across the room and deliver reliable service where you need it most. A lighted and covered On/Off switch helps prevent accidental shut-offs, while a 20-amp circuit breaker guards against dangerous circuit overloads. Its sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

### Features

**Multi-Outlet Power Distribution**

**Vertical or Horizontal Mounting**

**Extra Long Power Cord**

**Premium Safety Features**

**Heavy-Duty Housing**

### Highlights

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 12-in. mountable housing with 2 NEMA 5-15R and 2 NEMA 5-20R outlets and a 15-ft. (4.57 m) power cord
- Lighted, covered On/Off switch and 20-amp circuit breaker
- Sturdy construction and heavy-duty, all-metal housing

### Package Includes

- PS120420
- Mounting hardware
- Instruction manual

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332186126 |
| INPUT    |              |



Powering Business Worldwide

TRIPP LITE  
SERIES

|  |   |
|--|---|
| Nominal Input Voltage(s) Supported           | 120V AC   |
| Recommended Electrical Service               | 20A 120V  |
| Input Cord Gauge Type                        | 12 gauge; SJT   |
| Voltage Compatibility (VAC)                  | 120   |
| Input Plug Type                              | NEMA 5-20P  |
| Input Cord Length (ft.)                      | 15  |
| Right-Angle Plug                             | No  |
| Input Cord Length (m)                        | 4.57  |
| Integrated Cord Clip                         | No  |
| <b>OUTPUT</b>                                |   |
| Frequency Compatibility                      | 60 Hz   |
| Output (Watts)                               | 1800  |
| Output Receptacles                           | (2) 5-15R; (2) 5-20R  |
| Circuit Breaker (amps)                       | 20  |
| Transformer Accommodation                    | (2) Yes   |
| Right-Angle Outlets                          | No  |
| Outlet Spacing                               | 1.77 in center to center.   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Switches                                     | Lighted 2 position switch controls power to all outlets   |
| Locking Switch Cover                         | Transparent on/off switch cover prevents accidental turn-off  |
| <b>PHYSICAL</b>                              |   |
| Color  | Silver  |
| Material of Construction                     | Aluminum  |
| Power Cord Color                             | Black   |
| Form Factors Supported                       | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications |
| Housing Color                                | Silver  |
| Mounting Holes or Slots                      | No  |
| Outlets Measurement (Center to Center)       | 1.77 in.  |
| Receptacle Color                             | Black   |
| Shipping Dimensions (hwd / in.)              | 3.70 x 6.00 x 15.70   |
| Shipping Dimensions (hwd / cm)               | 9.40 x 15.24 x 39.88  |
| Shipping Weight (lbs.)                       | 3.60  |
| Shipping Weight (kg)                         | 1.63  |
| Unit Dimensions (hwd / in.)                  | 1.250 x 1.620 x 12.000  |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                |
|--------------------------------------|--------------------------------|
| Unit Dimensions (hwd / cm)           | 4.21 x 6.34 x 15.6             |
| Unit Weight (lbs.)                   | 2.75                           |
| Unit Weight (kg)                     | 1.25                           |
| Outlet Spacing                       | 1.77 in.                       |
| Mounting Details                     | Includes mounting clips        |
| <b>ENVIRONMENTAL</b>                 |                                |
| Operating Temperature Range          | 32° to 104°F (0° to 40°C)      |
| Storage Temperature Range            | 14° to 122°F (-10° to 50°C)    |
| Operating Humidity Range             | 10% to 90% RH                  |
| Storage Humidity Range               | 5% to 95% RH                   |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                |
| Antimicrobial                        | No                             |
| Built-In Circuit Breaker             | Yes                            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                |
| Product Certifications               | cUL Listed; UL 1363; UL Listed |
| Product Compliance                   | RoHS                           |
| <b>WARRANTY &amp; SUPPORT</b>        |                                |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty      |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.