

Safe-IT UL 2930 Medical-Grade Surge Protector for Patient Care Vicinity, 4x Hospital-Grade Outlets, 15 ft. Cord

MODEL NUMBER: SPS415HGULTRA



Full UL 2930 compliance and agency listing, surge protection, integrated locking safety covers and a 15 ft. cord make this medical-grade power strip ideal for standalone use inside and outside patient care vicinities.

Features

Power Distribution Anywhere in Any Medical Facility Ideal for standalone use in all patient care vicinities, therapy rooms, imaging environments, laboratories and administrative areas. 120V 60Hz power strip complies with UL 2930 specifications. Access product specifications instantly with QR code integration ensuring critical documentation is available when and where it's needed. Automatic single-fault protection.

Exclusive Antimicrobial Protection Antimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildew.

Versatile Medical-Grade Solution 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power. 15 ft. power cord with NEMA 5-15P-HG plug provides ample reach to the power source. Aluminum housing for long life in demanding environments.

Premium Safety Features 1620 joules of surge suppression protect against dangerous power spikes. Integrated locking outlet safety covers block access to unused outlets. Switchless design prevents accidental shut-off. LED indicates power is present and surge-protected.

Ready to Use Right Out of the Box Built-in mounting slots and flanges for easy installation on a variety of surfaces.

Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Approved for standalone use in all patient care vicinities
- Complies with UL 2930 and NFPA 99 specifications
- 1620 joules of surge suppression protects essential electronics
- 4 NEMA 5-15R-HG hospital-grade outlets with locking safety covers

Package Includes

- SPS415HGULTRA UL 2930 Medical-Grade Surge Protector
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332159236
INPUT	
Nominal Input Voltage(s) Supported	120V AC



Powering Business Worldwide

TRIPP LITE
SERIES

Recommended Electrical Service	15A, 120V/125V
Voltage Compatibility (VAC)	120; 125
Maximum Surge Amps	60000
Input Plug Type	NEMA 5-15P-HG
Input Cord Length (ft.)	15
Right-Angle Plug	No
Input Cord Length (m)	4.57
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1875
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1620
Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No
PHYSICAL	
Material of Construction	Aluminum
Power Cord Color	White
Housing Color	White
Mounting Holes or Slots	Yes
Outlets Measurement (Center to Center)	81.6MM
Receptacle Color	White
Shipping Dimensions (hwd / in.)	13.19 x 6.50 x 0.50



Powering Business Worldwide

TRIPP LITE
SERIES

Shipping Dimensions (hwd / cm)	33.50 x 16.51 x 1.27
Shipping Weight (lbs.)	3.24
Shipping Weight (kg)	1.47
Unit Dimensions (hwd / in.)	11.020 x 2.500 x 1.790
Unit Dimensions (hwd / cm)	28 x 6.35 x 4.45
Unit Weight (lbs.)	2.69
Unit Weight (kg)	1.22
Mounting Details	MOUNTING BRACKET AND KEYHOLES
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	14° to 122°F (-10° to 50°C)
Operating Humidity Range	10% to 90% RH
Storage Humidity Range	5% to 95% RH
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	Yes
Mounting Accessory Included	Yes
Antibacterial	No
STANDARDS & COMPLIANCE	
Product Certifications	UL 2930
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.