

Use optional WEBCARDLXE web card  
Not compatible with WEBCARDLX

## SmartOnline 1000VA 900W 208/230V Double-Conversion UPS - 8 Outlets, Extended Run, Network Card Option, LCD, USB, DB9, 2U Rack/Tower

MODEL NUMBER: SUINT1000LCD2U



Provides pure sine wave output in education, healthcare, military, government and other IT applications in small or mid-size networks.

### Features

#### Double-Conversion UPS Protects Equipment Against Damage, Downtime and Data Loss

This on-line double-conversion UPS system maintains perfect output by converting AC input to DC, then reconverting UPS output to fully regulated sine wave AC. Constant on-line operation completely isolates sensitive equipment from every power problem on the AC line. The SmartOnline® SUINT1000LCD2U provides the highest level of power protection and battery backup for education, healthcare, military, government and other mission-critical IT applications where space is limited, but premium power reliability is essential.

#### Reliable, Expandable Battery Backup Keeps You Operational Through Power Outages

The field-replaceable, hot-swappable VRLA battery modules allow you to work through short power failures and give you enough time to safely save files and shut down your system in case of a prolonged blackout. Zero transfer time between on-line and battery modes maintains continuous operation of connected equipment without interruption or rebooting. Extra runtime is available by connecting up to four optional extended battery modules (BP48RT, sold separately).

#### Optional LX Platform Network Management Card Allows Remote Access 24/7

The WEBCARDLXE network interface (sold separately) enables full remote configuration and management, including load shedding, reboots of connected equipment and safe shutdowns. The IP-based Auto Probe feature ensures continuous network uptime by communicating with other network devices, detecting lost connectivity and automatically rebooting IT equipment. Optional EnviroSense2 modules (E2MT, E2MTDO and E2MTHDI, all sold separately) provide a variety of environmental monitoring and control options.

#### C13 Outlets Protect Your Connected Components

Eight C13 outlets provide connected equipment with pure sine wave AC output and allow you to manage power consumption down to the outlet group level. Power provided by these outlets is filtered to protect connected equipment against damaging surges and line noise. Four outlets are grouped into two load banks that let you shed non-critical loads to extend runtime for critical loads.

### Highlights

- <li style="line-height: 12px;margin-bottom: 7px;">Updated design for 2025</li>
- <li style="line-height: 12px;margin-bottom: 7px;">Protects equipment against blackouts, brownouts, transient surges and line noise</li>
- <li style="line-height: 12px;margin-bottom: 7px;">Keeps equipment running during outages to allow time for file saves and safe shutdown</li>
- <li style="line-height: 12px;margin-bottom: 7px;">Zero transfer time between on-line and battery modes for uninterrupted operation</li>
- <li style="line-height: 12px;margin-bottom: 7px;">ENERGY STAR 2.0-certified to save electricity, lower costs and protect the environment</li>
- <li style="line-height: 12px;margin-bottom: 7px;">Menu-driven LCD keeps you up to date with status info and other vital analytics</li>
- <li style="line-height: 12px;margin-bottom: 7px;">Compatible with Eaton Tripp Lite power cords to simplify deployment and enhance reliability</li>

### Package Includes

- 1000VA 900W 208/230V Double-Conversion UPS
- USB cable
- DB9 cable
- (2) IEC 10A 6ft. output cables
- Rack-mounting hardware
- Tower support stands
- Safety instructions
- Quick start guide



Powering Business Worldwide

TRIPP LITE  
SERIES

**Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better**

This UPS system filters out disruptive electromagnetic and radio frequency interference that can inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

**ENERGY STAR-Certified to Help You Save Money and Protect the Environment**

By meeting strict U.S. Department of Energy and U.S. Environmental Protection Agency requirements, this ENERGY STAR 2.0 UPS system provides high operational efficiency to signal a reduction in BTU emissions, save on utility and cooling costs and help protect the environment.

**Clear LCD Interface Keeps You Informed at a Glance**

The menu-driven front-panel LCD provides detailed alarms and notifications to help diagnose any issues. It provides system status, event logs, battery and power module status, usage analytics, serial number, firmware update info and more. Audible alarms can be disabled through the front menu when the UPS goes to battery power. The LCD rotates to accommodate both rack-mount and tower installation.

**Advanced Communications Ports Allow for Automatic Saves and Shutdowns**

RS-232 and USB ports connect to a device for a variety of communication options (cables are included). A dry-contact relay port can be programmed through the LCD to provide reliable communications to automation and industrial components. The RPO/ROO port permits emergency shutdown or remote restart of all connected equipment.

**Versatile Installation Options**

You can mount the SUINT1000LCD2U in just 2U of space in an EIA-standard 19-inch rack using the included hardware. You can also adapt it for tower installation using the included support stands. The C14 power inlet accepts a variety of user-supplied input cords.

## Specifications

OVERVIEW	
UPC Code	037332185648
UPS Type	On-Line
INPUT	
Input Phase	Single-Phase
Rated input current (Maximum Load)	6A
Nominal Input Voltage(s) Supported	200V AC; 208V AC; 220V AC; 230V AC; 240V AC
UPS Input Connection Type	C14 inlet
Maximum Input Amps	6
Input Frequency	40-70Hz before transfer to battery
Input Current	6A
Power Factor (Input)	0.99
OUTPUT	
Output Capacity (VA)	1000
Output Capacity (kVA)	1
Output Capacity (Watts)	900



Powering Business Worldwide

TRIPP LITE  
SERIES

Output Capacity (kW)	0.9
Output Capacity Details	220/230/240V: 1000VA / 1000W; 208V(default)/200V: 1000VA / 900W
Power Factor	0.9
Crest Factor	3:1
Nominal Voltage Details	208V default
Frequency Compatibility	50 / 60 Hz
Frequency Compatibility Details	Online Mode: Sync with line $\pm 5\%$ of nominal line frequency (outside this range: $\pm 0.5\%$ of auto-selected nominal frequency). Battery Mode: $\pm 0.5\%$ of auto-selected nominal frequency
Output Voltage Regulation (Line Mode)	+/- 1%
Output Voltage Regulation (Economy Line Mode)	+/- 1%
Output Voltage Regulation (Battery Mode)	+/- 1%
Output Receptacle Details	Compatible with Eaton Tripp Lite Power Cords
Included Output Power Cables	(2) IEC 10A 6ft. output cables
Load Management Receptacles	Two switchable two-outlet load banks
Output AC Waveform (AC Mode)	Pure Sine wave
Output AC Waveform (Battery Mode)	Pure Sine wave
Nominal Output Voltage(s) Supported	200V; 208V; 220V; 230V; 240V
Output Receptacles	(8) C13
Individually Controllable Load Banks	Yes
<b>BATTERY</b>	
Battery Type	Valve Regulated Lead Acid (VRLA)
Runtime Full Load (min.)	7.3 min. (900W)
Runtime Half Load (min.)	17.9 min. (450W)
Expandable Runtime	Yes
Expandable Runtime Description	Add up to 4 extended battery modules (EBM). Part number <a href="#">BP48RT</a> . *Note: <a href="#">BP48RT</a> is only compatible with the 2025 UPS design update featured on this page. For previous design battery pack functionality, please see the Legacy Product Datasheet in the Documents & Downloads section below.
External Battery Pack Compatibility	<a href="#">BP48RT</a>
DC System Voltage (VDC)	48
Battery Recharge Rate (Included Batteries)	3 hours recharge to 90%
Battery Access	Battery access door





Powering Business Worldwide

TRIPP LITE  
SERIES

Shipping Dimensions (hwd / cm)	24.00 x 55.02 x 60.02
Shipping Weight (lbs.)	51.81
Shipping Weight (kg)	23.50
UPS Housing Material	Metal
Unit Dimensions (hwd / in.)	3.410 x 17.330 x 17.720
Unit Weight (lbs.)	36.38
Unit Weight (kg)	16.50
Mounting Details	4 post installation accessories included
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	With battery: 32° to 104°F (0° to 40°C); without battery: -13° to 131°F (-25° to 55°C)
Relative Humidity	0 to 96%, non-condensing
AC Mode BTU / Hr. (Full Load)	267
AC Economy Mode BTU / Hr. (Full Load)	96
AC Mode Efficiency Rating (100% Load)	0.912
AC Economy Mode Efficiency Rating (100% Load)	0.97
Online Mode Heat Dissipation (BTU/Hr) @ Full Load	267
Battery Mode Heat Dissipation (BTU/Hr) @ Full Load	438
Operating Elevation	0-10000 ft. (0-3000 m)
Audible Noise	40dBA
<b>COMMUNICATIONS</b>	
Network Management Cards	(1) <a href="https://tripplite.eaton.com/Network-Card-Eaton-Tripp-Lite-Series-UPS-Systems-WEBCARDLXE">WEBCARDLXE</a>
Network Monitoring Port Description	WEBCARDLXE Supports detailed monitoring of UPS and site power conditions; DB9 port supports RS232 and contact closure communications; not compatible with WEBCARDLX
PowerAlert Software	For local monitoring via the UPS's built-in communication ports, download PowerAlert software at <a href="https://tripplite.eaton.com/products/power-alert">https://tripplite.eaton.com/products/power-alert</a>
Communications Cable	USB and RS232 cable included
WatchDog Compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
Network Management Card Description	Network management card optional
Communications Interface	(1) Contact closure; (1) RS-232; (1) Slot for SNMP/Web interface; (1) USB
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	0 ms.



Powering Business Worldwide

TRIPP LITE  
SERIES

FEATURES & SPECIFICATIONS	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
High Availability UPS Features	Expandable battery backup; Hot swappable batteries; On-Line/Double-Conversion; Pure sine wave output; Remote management; Surge/noise protection; Zero transfer time
Green Energy-Saving Features	High efficiency economy mode operation; Individually controllable load banks
APPLICATIONS	
UPS Applications	Mission Critical Applications
STANDARDS & COMPLIANCE	
Product Certifications	CAN/CSA-C22.2 No. 107.3 (Canada); NOM (Mexico); UL 1778; cTUVus
Product Compliance	CE (Europe); ENERGY STAR Qualified; RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 & <a href="https://tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>
Extended Service Plans	5-year depot exchange plan: TL9SW5Y-1500UC Expedited parts coverage for 5 years Parts, electronics and UPS batteries coverage Next business day shipping Technical support 5-year onsite plan: TLWFLN75XX-2509UC Onsite parts and labor coverage for 5 years Parts, electronics and UPS batteries coverage 24x7 onsite labor coverage, next-day response Next-day shipping Technical support

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.