

# EXO Slim Tag

## Wafer-thin UHF or HF/UHF asset tags for containers or metallic equipment



HID EXO Slim Tag transponders are the ideal solution for tagging shipping containers or other metallic assets. Some models being less than two-tenths of an inch (3 mm) thick, these tags mount flush to any surface. The high impact polycarbonate housings shield internal components from the environmental extremes and rugged treatment of industrial freight operations.

This versatile range of tags provides more ruggedization than standard on-metal labels and includes both global and regional options. The EXO Slim range provides cost effective solutions for volume applications in manufacturing and industry – especially for tracking and managing IT office assets, portals and returnable transport items (RTI's). There is a wide choice in terms of label size, read range, printing options and encasement alternatives.

Standard grey EXO Slim InLine Plate Tags provide excellent contrast for imprinting. The large surface accommodates embossing, laser-engraving or adhesive labels for a logo, barcode, serial number or text message.

Tough and versatile, EXO Slim Tag transponders are available for mounting on metal, plastic or wood using standard nails, screws or industrial adhesives.

The tags are lightweight, dust tight, waterproof and protected against close-range high pressure, high temperature spray downs (IP69K) for some models.

EXO Slim Tag UHF improve data collection speed and accuracy for logistics applications, while making tracking more cost-effective. The plates can be read from distances of up to a 49 ft (15 m), and are compliant with EPC global-certified UHF Class 1 Gen 2 readers and modules.

EXO Slim SHELL low-profile RFID tags are ideal for light duty indoor assets tracking. SHELL+ tags are ultrasonic sealed with a plastic back side to screw, while SHELL tags come with a sticker instead of the plastic cover on the back for easy application. Their transparent housing protects the barcode inside from scratches and allows tags to be applied to metallic and non-metallic surfaces.

In short, EXO Slim tags provide the durability of an encased RFID tag in a small footprint for harsh environments with some of the options in the range being the most rugged tags on the market, even withstanding a "sledgehammer test".



### KEY BENEFITS:

- **Durability** – Resistant to outdoor elements as well as blunt and sharp impact.
- **Versatility** – Thin plates mount flush with glue or screws to any material.
- **Visibility** – Large surface may be printed or laser-engraved with logo, barcode, serial number or text.

### TECHNOLOGY HIGHLIGHTS:

- RAIN UHF Worldwide operating frequencies from 860 to 960 MHz (off-metal) or specialized (on-metal)
- Fully interoperable; standards-compliant
- Reliable performance on both metal and non-metal surfaces
- Waterproof under high pressure and temperature; chemical and impact resistant
- Mount with glue, nails, or screws
- Versatile print/encasement options including clear rugged covers allowing visibility of human readable print or barcode on the label itself

## APPLICATION AREAS:

### Outdoor Asset Tracking and Logistics

- Postal and road toll management: truck, wagon and train tracking
- Supply chain management: pallet and goods tracking

### Automation and Manufacturing

- Materials and inventory and tracking

### Returnable Transport Items

- Shipping container tracking








- Tracking and monitoring plastic trays used in manufacturing conveyor systems

### Waste Management

- Commercial and industrial bin identification

### Indoor Asset Tracking

- Transparent SHELL+ and SHELL tags are ideal for light duty indoor assets tracking like furniture or compartments. Supports CMMS (Computerized Maintenance Management System) via NFC

	EXO Slim						
	InLine Plate	1200P	800P	750P	600 SHELL+	1000 SHELL+	1200 SHELL+
							
Base Model Number	6C698A (EU) 6C698B (US)	CP19038	CP15940	CP19723	CP14519 (EU) CP14522 (US)	CP18881 (EU) CP18890 (US)	CP17190
ELECTRONIC							
Operating Frequency	(EU) - 865-868 MHz (ETSI) / (US) - 902-928 MHz (FCC)		865-928 MHz (Global)		(EU) - 865-868 MHz (ETSI) / (US) - 902-928 MHz (FCC)		865-928 MHz (Global)
Chip Type	Monza 4E	M730			Monza R6-P	M730	
Memory	496 bit EPC + 96 bit TID + 128 bit user	128 bit EPC 48 bit TID			28/96 bit EPC, 32/64 bit UM	128 bit EPC + 48 bit TID	
Anti-Collision	Yes						
Reading Distance (2W reader ERP, free space)	Up to 26 ft (8 m) off-metal; 20 ft (6 m) on-metal	Up to 41.9 ft (12.8 m)	Up to 49 ft (15 m)	Up to 36 ft (11 m)	Up to 25.2 ft (7.7 m)	Up to 18.3 ft (5.6 m)	Up to 34.7 ft (10.6 m)
PHYSICAL							
Dimensions	4.7 x 2.7 x 0.14 in (120 x 68 x 3.7 mm)	5.99 x 0.58 x 0.17 in (152.3 x 14.8 x 4.4 mm)	4.1 x 1.4 x 0.14 in (105 x 36 x 3.5 mm)	3.38 x 0.94 x 0.12 in (86 x 24 x 3 mm)	3.38 x 0.78 x 0.28 in (86 x 20 x 7.3 mm)	3.5 x 1.10 x 0.32 in (89 x 28 x 8.3 mm)	4.84 x 1.29 x 0.26 in (123 x 33 x 6.8 mm)
Mounting Method	Glue, nail or screw	Adhesive, Glue, nail or screw		Glue, nail or screw			
Screw Fixation Hole	Ø 0.16 in (4.2 mm)	Ø 0.13 in (3.5mm)	Ø 0.17 in (4.4 mm)	Ø 0.12 in (3.2mm)	Ø 0.12 in (3.2 mm)		
Affixes To	All surfaces, including metal, plastic, wood		Off Metal, plastic, wood		All surfaces, including metal, plastic, wood		
Housing Material	PC/ABS high impact	PC	ABS	PC			
Color	Pantone warm gray 2U	White	Gray	Transparent			
Weight	1.0 oz (27 g)	0.24 oz (7 g)	0.4 oz (11.6 g)	0.24 oz (6.7 g)	0.32 oz (9 g)	0.42 oz (12 g)	0.7 oz (20 g)
CHEMICAL AND MECHANICAL RESISTANCE							
Water	IP69K, 176° F (80° C), 100 bar, 30 sek. 16 l/min		IP68, 6.6 ft. (2 m) x 24 h				
Withstands Exposure To	Mineral oil, petroleum, salt mist, vegetable oil	168 hr: 10% salt water, vegetable oil up to 80% humidity at 158° F (70° C), motor oil 24 hr: acetone	5% caustic soda, 10% salt water, vegetable oil, Motor oil 68° F (20° C), 168hr (for 800P to 1200 Shell+)				
Vibration & Shock	IEC 68.2.6 / IEC 60068-2-27:2008		MIL-STD-810 G				
Impact	IEC 62262-IK06		1.2 m drop on concrete	1 kg Steel, 1 m			
Axial/Radial Force	500 N, 10 sec						
THERMAL							
Storage	-40° to +185° F (-40° to +85° C), 1 x 1000 h		-40° to +185° F (-40° to +85° C)	-4° to +185° F (-20° to +85° C)	-22° to +149° F (-30° to +65° C)		
Operating	-40° to +185° F (-40° to +85° C)			-4° to +185° F (-20° to +85° C)	-22° to +149° F (-30° to +65° C)		
Shock/Fatigue	-40° to +185° F (-40° to +85° C), 100 x 5 min with 30 sec transition						
OTHER							
Standards	UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364		UHF EPC Class 1 Gen 2, ISO 18000-6C, ISO 17364				
Options	Embossing or laser-engraving of logo, barcode or text. (Standard tags have no laser-engraving.)				Also available as SHELL with adhesive liner instead of hard back cover. See individual spec sheet for details		
Box Size	60 pcs.	280 pcs.	720 pcs.	1300 pcs.	936 pcs.	810 pcs.	448 pcs.
Warranty	2 Years						

