

Epoxy Tag

Micro thin RFID tags that withstand extreme environments



HID Epoxy Tag RFID transponders are constructed for optimal performance under harsh conditions.

Epoxy housings protect advanced integrated chips, enabling the use of RFID technology to accelerate logistics speed while improving data accuracy in a broad spectrum of rugged industrial applications.

Epoxy Tag units are resistant to fuels, mineral oils, petroleum and salt mist. They repel moisture – even in high temperature, high pressure washes.

Unrelenting performance despite temperature fluctuations allows Epoxy Tag transponders to adapt to demanding applications. These tags can tolerate repeated autoclaving

in medical applications, and plastic injection molding processes for permanent embedding into industrial components, equipment or containers.

Each micro thin Epoxy Tag device has a smooth surface, which may be imprinted with customized visual codes or artwork.

Epoxy Tag transponders are available in a variety of shapes and sizes, and may be adhered with glue, secured with screws, or embedded in a custom housing, depending on the application.

The Epoxy Tag Keyfob features a unique chip that optimizes NFC program security, utility, and ease-of-implementation when deployed with HID Trusted Tag® Services, a cloud-based authentication platform that adds a non-replicable identity to each interaction.

In addition, HID can create a custom Epoxy Tag solution to fit any application requirements for chip type, dimensions or programming.



KEY BENEFITS:

- Durable – resists moisture, oils, petroleum; tolerates mechanical vibration and shock
- Thermally stable – withstands exposure to temperatures from -40° F to 284° F (-40° to 140° C)
- Surface printable – enables tags scannable by both RFID and visual ID readers

TECHNOLOGY HIGHLIGHTS:

- Operating frequencies
 - LF 125 kHz
 - HF 13.56 MHz (NFC)
 - RAIN UHF 865-956 MHz worldwide
- Withstands peak temperatures up to 284°F (140°C)
- Large, read-write memory
- Chemical and moisture resistant
- Printable surface

For more information, contact tagsales@hidglobal.com

Epoxy Tag






HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

APPLICATION AREAS:

- **Automation and manufacturing**
 - Item/box tracking through production process
 - Electronic tool identification
- **Medical and health**
 - Sterilization validation
 - Equipment identification
- **Waste management/RTI**
 - Usage-based invoicing
 - Recycling incentive programs
 - Returnable transport items
 - Asset tracking and logistics
- **Marketing**
 - Loyalty programs
 - Promotions
 - Stored-value
 - Proof of presence

Epoxy Tag

| | LF Disc | HF | UHF |
|-------------------------------|---|---|---|
| | 30 mm | Keyfob | |
| |  |  |  |
| Base Model Number | 601143 -001 | 6D6140-101 | 6M6970-101, 6H2970 (MR6-P) |
| | ELECTRONIC | | |
| Operating Frequency | 125 kHz | 13.56 MHz | 865-928 MHz (Global) |
| Chip Type | Unique | HID Trusted Tag* | M730, MR6-P |
| Memory | 64 bit read-only | 8 KB | 128 bit EPC |
| Anit-collision | | | Yes |
| Reading Distance | Dependent upon reader, environment and application | Proximity (NFC Tap) | 20 ft (6 m) |
| | PHYSICAL | | |
| Dimensions | Ø 1.18 x 0.04 in (Ø 30 x 1 mm) | 1.2 x 1.8 x 0.06 in (30 x 45 x 1.6 mm) | 3.3 x 1.0 x 0.04 in (83 x 25 x 1 mm) |
| Mounting Method | Glue, screw-on, or encapsulate | | |
| Fixation Hole Size | Ø 0.13 in (Ø 3.2 mm) | Ø 0.2 in (Ø 5 mm) | Ø 0.12 in (Ø 3.0 mm) |
| Affixes To | Glass, plastic, wood | | |
| Housing Material | Epoxy | | |
| Color | Black | | |
| | CHEMICAL AND MECHANICAL | | |
| Water | P68, IP69K, 176° F (80° C), 100 bar x 30 sec | | |
| Withstands Exposure To | Fuel B, mineral oil, petroleum, salt mist, vegetable oil | | |
| Environmental Test Conditions | 68° F (20° C), 100 h | | |
| Vibration | IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h] | | |
| Shock | IEC 60068-2-27:2008 [40 g, 18 ms, 6 axis, 2000 times] | | |
| Drop Test | 100 drops 5.9 ft (1.8 m) | | |
| | THERMAL | | |
| Storage | -40° to +185° F (-40° to +85° C), 1000 h | | |
| Operating | -40° to +185° F (-40° to +85° C) | | |
| Shock/Fatigue | -40° to +194° F (-40° to +90° C), 100 x 5 min with 30 sec transition | | |
| Peak | 284° F (140° C), 24 h | | |
| | OTHER | | |
| Standards | | ISO 14443A - NFC Tag Type 4 | ISO/IEC 18000-6C; EPC Global Class 1 Gen 2 |
| Options | Custom printing or laser engraving; custom sizes; self-adhesive; or alternative chips e.g. MIFARE, NTAG | | |
| Box Size | 500 pcs. | 250 pcs. | 1.000 pcs. |
| Warranty | 2 Years | | |

* Encoded by HID with your unique Trusted Tag® Services identity.

