

Sentry PCB Tag

Highly Configurable, PCB Based RFID Tags with Exceptional Size-to-Performance Ratio



HID Sentry PCB tags are small footprint, low profile, RFID tags that provide exemplary read range for tags that are so small in size and have minimal ergonomic impact.

Because of its low profile, it is unlikely to be dislodged by rough handling when applied to assets like weapons, hand tools and other small metal parts.

The unique construction of these tags provides a very high level of impact, vibration and temperature resistance. Sentry tags are also resistant to a very wide range of chemicals and have an ingress protection rating of IP 68. Sentry products can easily be adapted for applications involving over-molding and over-spraying or embedding in metal.

HID RFID's Sentry line of high-performance, cost-effective and application-specific RFID tags are based on a printed

circuit board platform. This well-established manufacturing process offers unsurpassed reliability and consistency in read range performance. At the core of the tag is a fiber-reinforced composite material that gives the Sentry tag its innate ruggedness. The innovative, patented tag design enables fast prototyping and affordable customization — essential to the expanding requirements of the RFID industry.

The optionally available **Sentry Pro** version of some models features a reinforced design and adhesive sticker to support over 1,000 autoclave sterilization cycles (~138°C), which is more than what most tagged instruments need to endure in terms of repeated extreme temperature cycling. Alternatively, there is the option to further upgrade the Sentry Pro tags to polyimide substrate which increases the maximum endured temperature of Sentry Pro tags up to 464 °F (240°C).

Sentry Instrument is a special variant with an ultra-low profile optimized for long metallic tools like medical instruments or scissors.

e-Module transponders provide high frequency (HF) coils in a robust housing, to withstand the high heat manufacturing processes of special finished tags.



KEY BENEFITS:








- **High performance** – Small hard tags with great read range when mounted on metal (UHF)
- **Rugged** – Tolerates repeated exposure to high temperatures, vibration and impact
- **Autoclave-resistant** – Pro models survive over 1,000 autoclave disinfections

KEY TECHNOLOGY HIGHLIGHTS:







- Includes latest Impinj chipsets, optimized for EU or US (UHF versions)
- Reads distances up to 33 ft (10 m)
- Provides outstanding size-to-performance ratio with small footprint and low profile

TYPICAL APPLICATION AREAS:

- Surgical/medical/dental instrument tracking
- Tool tracking
- Weapons management
- Rental asset tracking
- IT asset management

	Sentry PCB Tag						
	Sentry e-Module	Sentry ARI0 XS-SM	Sentry 5706 - FIT 210	Sentry 4607	Sentry 2505	Sentry Duo	Sentry Shortie
							
Base Model Number	629601	TM370E11	CP10258 (EU) CP10257 (US)	AST1-135-0310 (EU) AST1-135-0300 (US)	AST1-161-0310 (EU) AST1-161-0300 (US)	AST1-160-0310 (EU) AST1-160-0300 (US)	AST1-183-0310 (EU) AST1-183-0300 (US)
	ELECTRONIC						
Operating Frequency	13.56 MHZ		865-868 MHZ (ETSI) / 902-928 MHZ (FCC)				
Chip Type	ICODE SLIX	ICODE SLIX-S	Higgs 3	M750			
Memory	1024 bit EEPROM	2048 bits EEPROM	512 bit user memory + 96 bit EPC + 64 bit TID	96 bit EPC 32 bits UM			
Anti-collision	Yes						
Reading Distance	Dependent upon reader, environment and application		6.6 ft (2 m)	13 ft (4 m)	11 ft (3.5 m)	18 ft (5 m)	12.5 ft (3.8 m)
	PHYSICAL						
Dimensions	Ø 0.57 in (14.5 mm)	0.53 x 0.55 in (13.6 x 13.9 mm)	2.25. x 0.23 x 0.05 in (57.1 x 5.95 x 1.3 mm)	1.8 x 0.28 x 0.07 in (46 x 6.9 x 1.7 mm)	0.98 x 0.21 x 0.09 in (25 x 5.3 x 2.4 mm)	1.43 x 0.43 x 0.11 in (36.3 x 10.9 x 2.8 mm)	1.03 x 0.43 x 0.11 in (26 x 10.9 x 2.8 mm)
Mounting Method	Embed, glue		Film Adhesive (included)	Adhesive Sticker	Epoxy, adhesive sticker optional	Adhesive sticker / slot for zip-tie	Adhesive sticker
Affixes to	Non-metal		Metal surfaces			Any surfaces	Metal surfaces
Housing Material	PCB						
Color	Yellow + antenna	Black + antenna	Red	Black (with White Label)			
Weight			0.03 oz (1 g)	0.05 oz (1.5 g)	0.03 oz (1 g)	0.07 oz (2 g)	
	CHEMICAL AND MECHANICAL RESISTANCE						
Water	Depends on finished product		IP68, 68° F (20° C), 1 m x 24 h				
Withstands Exposure To	Depends on finished product		Fuel B, mineral oil, petroleum, salt mist, vegetable oil	Dilute mineral acids, dilute alkali solutions (<20%), alcohols, petroleum, salt mist, vegetable oil, hydraulic fluid and most industrial cleaning agents			
Environmental Test Conditions			68° F (20° C), 100 h				
Vibration & Shock	Depends on finished product		IEC 68.2.6 / IEC 68.2.29				
Impact				18 in (46cm) drop with 1 in (2.54 cm) diameter steel ball			
	THERMAL						
Storage	-40° to 257°F (-40° to 125°C)		-40° to +185° F (-40° to +85°C)	-58° to 185° F (-50° to 85° C)			
Operating	-40° to +185° F (-40° to 85° C)		-40° to +185° F (-40° to +85°C)	-58° to 185° F (-50° to 85° C)			
Shock/Fatigue	-40° to +212° F (-40° to +100° C) , 10 x 1h with 10 sec transition						
Autoclave				Sentry Pro tags resist over 1.000 standard autoclave cycles up to 280°F (138°C), including elevated pressure and steam . Further upgrade to polyimide substrate possible on request increasing max. temperature to 464 °F (240°C).			
Peak Temperature			437° F (225° C)	365° F (185° C), 3 h			
	OTHER						
Standards	ISO 15693, ISO 18000-3, NFC Type V		EPC C1G2, ISO 18000-6C, RAIN				
Options	Custom programming on request			Can be upgraded to Sentry Pro version resisting over 1.000 Autoclave cycles incl. high-temperature adhesive sticker (end of P/N changes from -03x0 to -A3x0). Other specs remain the same. Tags come by default with HID standard label except e-module, FIT, 06D and Instrument tags. Custom labelling and/or programming on request. (PN changes from -03x0 to -03x1)			
Quantity Per Box	200 pcs.	1000 PCS.	3000 pcs.	150 pcs.			
Warranty	2 Years						



	Sentry PCB Tag					
	Sentry Slim	Sentry 06D	Sentry 1005	Sentry 2607	Sentry MidRange	Sentry Instrument
						
Base Model Number	AST1-162-0310 (EU) AST1-162-0300 (US)	AST1-162-0310 (EU) AST1-162-0300 (US)	AST1-140-0310 (EU) AST1-140-0300 (US)	AST1-154-0310 (EU) AST1-154-0300 (US)	AST1-174-0310 (EU) AST1-174-0300 (US) (bare tag, see EXO Pro for housed version)	28mm: AST1-137-0310 (EU); AST1-137-0300 (US) 15mm: AST1-167-0310 (EU); AST1-167-0300 (US) 11mm: AST1-171-0310 (EU); AST1-171-0300 (US)
	ELECTRONIC					
Operating Frequency	865-868 MHZ (ETSI) / 902-928 MHZ (FCC)					
Chip Type	M750					
Memory	96 bit EPC 32 bits UM					
Anti-collision	Yes					
Reading Distance	20 ft (6 m)	5 ft (1.5 m)	9 FT (2.7 M)	7 FT (2 M)	33 FT (10 M)	UP TO 8 FT (2.4 M)
	PHYSICAL					
Dimensions	1.43 x 0.43 x 0.11 in (36.3 x 10.9 x 2.8 mm)	Ø 0.24 in (6 mm)	0.39 x 0.2 x 0.12 in (10 x 5 x 3 mm)	1.02 x 0.28 x 0.06 in (26 x 7 x 1.5 mm)	1.52 x 0.67 x 0.22 in (38.6 x 17 x 5.6 mm)	1.06 or 0.6 or 0.49 x 0.07 x 0.05 in (27 or 15 or 12 x 1.8 x 1.4 mm)
Mounting Method	Adhesive sticker	Epoxy		Adhesive sticker		Epoxy
Affixes to	Metal surfaces					
Housing Material	PCB					
Color	Black (with White Label)	Black	Black (with White Label)			Black
Weight	0.06 oz (1.6 g)	0.02 oz (0.5 g)	0.03 oz (1 g)		0.22 oz (6.4 g)	28mm : 0.014 oz (0.4 g) 15mm : 0.010 oz (0.3 g) 11mm : 0.007 oz (0.2 g)
	CHEMICAL AND MECHANICAL RESISTANCE					
Water	IP68, 68° F (20° C), 1 m x 24 h					
Withstands Exposure To	Dilute mineral acids, dilute alkali solutions (<20%), alcohols, petroleum, salt mist, vegetable oil, hydraulic fluid and most industrial cleaning agents					
Environmental Test Conditions	68° F (20° C), 100 h					
Vibration & Shock	IEC 68.2.6 / IEC 68.2.29					
Impact	18 in (46cm) drop with 1 in (2.54 cm) diameter steel ball					
	THERMAL					
Storage	-58° to 185° F (-50° to 85° C)					
Operating	-58° to 185° F (-50° to 85° C)					
Shock/Fatigue	-40° to +212° F (-40° to +100° C) , 10 x 1h with 10 sec transition					
Autoclave	Sentry Pro tags resist over 1.000 standard autoclave cycles up to 280°F (138°C), including elevated pressure and steam. Further upgrade to polyimide substrate possible on request increasing max. temperature to 464 °F (240°C).					
Peak Temperature	365° F (185° C), 3 h					
	OTHER					
Standards	IEPC C1G2, ISO 18000-6C, RAIN					
Options	Can be upgraded to Sentry Pro version resisting over 1.000 Autoclave cycles incl. high-temperature adhesive sticker (end of P/N changes from -03x0 to -A3x0). Other specs remain the same. Tags come by default with HID standard label except e-module, FIT, 06D and Instrument tags. Custom labelling and/or programming on request. (PN changes from -03x0 to -03x1)					
Quantity Per Box	150 pcs.					
Warranty	2 Years					



For more global phone numbers [click here](#)

© 2022 HID Global Corporation/ASSA ABLOY AB.
All rights reserved.

2022-08-25-idt-rfid-sentry-pcb-ds-en PLT-06686

Part of ASSA ABLOY