

smartMICRO (Android)

SLS part # 10000252

The SLS smartMICRO™ plugs directly into your micro USB port and instantly turns your Android® powered device into an EPC Class 1 Gen2 UHF (RAIN) RFID reader; as it draws power via the USB Micro port, no external power supply or charging is required. The SLS smartMICRO™ provides users with the ability to read and write EPC Gen2 compliant tags. smartMICRO™ is very convenient to use where reading tags at close range is acceptable.

Contact us to receive the smartRFID library and API which provides Android® market app software developers the tools to create custom apps. You can also download smartREADER and smartEIT apps from Google Play store to start using smartMICRO™ on your Android® mobile device immediately.

What's Included

- smartMICRO™ Android Micro USB UHF RFID Reader

Technical Specifications

- **Air Interface Protocol:** ISO 18000-63
- **Operating Frequency:** US 902-928 MHz
- **Antenna Type:** Integrated
- **RF Power:** +10dBm to +18dBm
- **Operating System:** Android
- **Data Interface:** Micro USB Type B
- **Dimensions:** 38 mm x 33 mm x 15 mm (1.50 inch x 1.30 inch x 0.59 inch)
- **IP Rating:** IP 54
- **Operating Temperature:** 0° to +40°C
- **Storage Temperature:** -10° to +85° C

1 (888) 238-1155 Inside USA • 1 (205) 383-2244 Outside USA
info@atlasRFIDstore.com • www.atlasRFIDstore.com

atlasRFIDstore.com