

SATO-Direct 100P

FACESHEET		
Basis Weight (lb/ream)	49	
Caliper Target (mils)	3.2	
Tensile MD Target (lb/in)	25	
Tensile CD Target (lb/in)	16	
Tear MD (grams)		
Tear CD (grams)		
Stiffness MD (grams)		
Stiffness CD (grams)		
Color	White	

ADHESIVE	
Description	Permanent
Caliper Target (mils)	0.6

LINER	
Description	40# White Kraft
Caliper Target (mils)	2.4
TOTAL CALIPER	
Caliper Target (mils)	6.2

ENVIRONMENT			
Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	32		
Service Temperature (°F)	-4	to	120

SPECIAL NOTES:

	\sim \sim	`	 ΓΥΡΕ
$\vdash \Delta$	(=)	νнь	 I Y P E

Paper Film

PRODUCT TYPE

Label Tag Receipt

IMAGING CAPABILITY

Direct Thermal Thermal Transfer - Wax Thermal Transfer - Wax/Resin Thermal Transfer - Resin Laser

AGENCY RECOGNITION

UL cUL **FSC** FDA.21 CFR 175.105

BPA Free

MAXIMUM OUTDOOR LIFE

For Indoor Use only <6 months <12 months <18 months 2 years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

9007027

LABEL MANUFACTURING, SERVICE & SALES UNITED STATES MEXICO CENTRAL AMERICA

CARIBBEAN CANADA

©2021 SATO America . All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners. 8/9/2021