SATO-Direct 200P

C304722128LS

FACESHEET	
Basis Weight (lb/ream)	51
Caliper Target (mils)	3.2
Tensile MD Target (lb/in)	28
Tensile CD Target (lb/in)	14
Tear MD (grams)	
Tear CD (grams)	
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

ADHESIVE	
Description	Tackified Acrylic Permanent
Caliper Target (mils)	0

LINER	
Description	40# White Kraft
Caliper Target (mils)	2.4

TOTAL CALIPER	
Caliper Target (mils)	0

ENVIRONMENT			
Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	32		
Service Temperature (°F)	-4	to	120

FACESHEET TYPE	
✓	Paper
	Film

PRODUCT TYPE	
✓	Label
	Tag
	Receipt

IMAGING CAPABILITY	
✓	Direct Thermal
	Thermal Transfer - Wax
	Thermal Transfer - Wax/Resin
	Thermal Transfer - Resin
	Laser

AGENCY RECOGNITION	
	UL
	cUL
✓	FSC
	FDA.21 CFR 175.105
✓	BPA Free

MAXIMUM OUTDOOR LIFE	
✓	For Indoor Use only
	<6 months
	<12 months
	<18 months
	2 years

SPECIAL NOTES:

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

©2021 SATO America . All rights Reserved.• Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

8/4/2021

1 (888) 238-1155 Inside USA • 1 (205) 383-2244 Outside USA
info@atlasRFIDstore.com • www.atlasRFIDstore.com
atlasRFIDstore.com