



- Print speeds up to 12 ips (format & carrier dependent)
- Prints on a wide variety of media
- High smudge & scratch resistance
- Prints at moderate print head energy heat settings

TECHNICAL DATA

| RIBBON PROPERTY | |
|-----------------------------|---|
| Base Material | Polyester Film |
| Ink Color | Black |
| Transmission Density | 1.95 |
| Back Coating | Yes |
| Total Thickness | Black < 9 µm Anti static build-up treated |
| PET Thickness | 4.5 µm |
| Optical Density | ≥ 2.1 D |
| Ink Melt Point | 185°F (85°C) |
| Recommended Substrates | Coated and uncoated paper, tag stocks, and synthetics |
| DURABILITY OF PRINTED IMAGE | |
| Smudge & Scratch Resistance | High |
| Storage Condition | 40°-90°F (5-35°C), 20-85% RH |
| Storage Life | 1 year after manufacturing |

Inventory, Shipping, Pharmaceutical, Cosmetics, Shelf-edge, Markdown, Lawn and Garden, Ingredient, Food Rotation, Work In Process, Rating Plates, Retail Labeling, Care Labels, Signage & Logos, Laboratory, Healthcare, Tags, Short Term Outdoor Applications, Conveyor Sorting, Chemical Drums

Please contact us if your application is not among these.

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

©2022 SATO America. All rights Reserved. Rev A • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.