

*physical made digital*




#### **BENEFITS:**

- » Fast integration and time-to-market
- » Unparalleled investment protection
- » Cost-effective and highly scalable
- » Common Blade technology:  
common size, connection method,  
and software interface with the  
SkyeModule M9 UHF reader for  
maximum design and solution  
flexibility

#### **FEATURES:**

- » Miniscule footprint - 49% smaller than a business card
- » Greatest tag compatibility with Tagnostic® and TagIQ™
- » Minimal power consumption and maximum read range
- » Software Adjustable Host Interfaces: UART (TTL), SPI, USB, I<sup>2</sup>C
- » 7 General Purpose I/O Pins
- » Peripheral devices for encryption algorithms and key storage
- » Simple and intuitive API

## SkyeModule M2



Secure 13.56MHz OEM Reader/Writer

#### **Product Overview**

The SkyeModule™ M2 combines the rich HF tag/protocol support and performance typical of SkyeTek reader modules with standards-based security that is currently used by the Department of Defense and financial services to deliver the following benefits:

**Investment protection** through SkyeTek's Advanced Universal Reader Architecture (AURA) which abstracts frequency, protocol, and tag selection from the application.

**Ease of integration** by using the SkyeAPI™, a single library that abstracts, simplifies, and automates tag and protocol-specific functions from the programmer.

**Tagnostic®** support for more ISO 15693 and 14443 A/B tags than any other comparable reader allowing customers to fully optimize their application.

**TagIQ™** that recognizes the unique characteristics of each tag so that read/write performance is maximized for each individual tag type.

**Performance optimization** achieved through best-in-class output power (200mW), noise reduction technology, and power management – essential embeddability measures.

**Industry-leading privacy protection and anti-counterfeiting/anti-tampering** that can be used with any generic tag saving 60–70% versus tags that use proprietary security.


**Support for standard and proprietary encryption** such as MIFARE and 3DES.

**Unprecedented price-performance and TCO**, best exemplified by licensing options that allow customers to manufacture modules at cost.

#### **Applications**

The SkyeModule M2 has been created specifically for several applications that share common requirements for tag support, protocol, performance, and security. The M2 is an optimal solution for the following:

- Product Authentication and Anti-counterfeiting
- Handheld Reading/Encoding
- Inventory Management
- Patron Management
- Asset Tracking
- Printing/Encoding



**About SkyeTek:**

SkyeTek, Inc continually strives to enable the pervasive adoption of RFID technology. SkyeTek's Tagnostic™ reader technology works with most industry standard tags and smart labels; its low power requirements and a small form factor make it the optimal choice for embedding into new or existing products. SkyeTek's RFID reader technology is available in several formats including reader modules, finished readers and hardware reference designs. SkyeTek markets to OEM customers in targeted vertical markets with several high-volume licensing options available.

**Software and Security**

**Software**

SkyeAPI C/.NET API  
SkyeTek Protocol v3  
SkyeWare 4 developer interface  
Demonstration applications

**SkyeOS™ Embedded**

TagIQ™  
Field upgradeable firmware bootloader

**SkyeOS Product Authentication**

Clone and tamper protection  
Counter & time-based policy support

**SkyeSecurity Encryption**

DES, 3DES & AES  
MIFARE and CryptoRF support

**SkyeSecurity Clone/Tamper Protection**

SHA & MD5 secure hashing  
Digital signature support  
Key Derivation Function (KDF)  
Pseudo-Random Number Generator (PRNG)  
Secure key store

**Minimum Select/Read/Write Transponder Support**

Air-Interface	Manufacturer	Product Family	Tags
ISO15693	NXP	ICODE	SLIX-/S/L, SLI-/S/L
ISO15693	TagSys	370 Series	370L-/HL/DL, 370S-DM
ISO15693	ST Micro	Long Range	LRI/1k/2k, LRIS/2k/64k
ISO15693	Infineon	Vicinity	SRF 55V/01P/02P/10P/02S/10S
ISO15693	Fujitsu	FerVID	MB89R11/9B/8C
ISO15693	Texas Instr	Tag-It	Standard, Pro, Plus
ISO15693	EM Micro	EM Series	EM4/033/133/233
ISO14443A	NXP	MIFARE	Classic/1k/4k, Ultralight/C, DESFire EV1
ISO14443A	Verayo	Vera	M1, M4
ISO14443B	ST Micro	Short Range	SRI/2k/4k/512, SRIX4k, SRT512

See the M2 Tag Support List located [www.skyetek.com/docs/M2/TagSupportMatrix.pdf](http://www.skyetek.com/docs/M2/TagSupportMatrix.pdf) for full list of supported features.

**Specifications**

**Frequency**

13.56 MHz ± 7 kHz

**Peripheral I/O Connection**

7 programmable GPIO pins  
ISO 7816 smart card slot (optional)

**Current Consumption**

Sleep Mode: 4 mA  
Idle Mode: 75 mA  
Scan Mode: 175 mA

**Physical**

	CF	MH
Length:	66 mm	70 mm
Width:	36 mm	53 mm
Height:	5 mm	9 mm
Weight:	8.7 g	10.5 g

**Compliance**

FCC 15.225 EN 300330  
EN 301-489 EN 61000-4-3  
AS/NZS 4268:2003 DGT LP002  
HKTA 1035 IDA TS SRD  
ETSI EN 300-330 (RED 2014/53/EU)

**Antenna Options**

Internal or 50 Ω MMCX (female) output for external connection

**Host Interfaces/Data Rates**

UART (TTL): 9.6-115.2 kbps  
SPI: Mode 1 up to 4 Mb/s  
USB: 2.0 Full Speed 12 Mb/s  
I<sup>2</sup>C: 100/400 kHz

**Transponder Communication Rate**

ISO 14443A: 106 kbps  
ISO 14443B: 106 kbps  
ISO 15693: 26 kbps

**Effective Range**

Vicinity, External Antenna: 16 cm  
Proximity, External Antenna: 8 cm

**Environment**

Storage Temperature: -20°C to 85°C  
Operating Temperature: -10°C to 70°C

**Air-interface Protocols**

ISO 14443 A/B (parts 2-4)  
ISO 15693

(read range and rate are subject to specific environmental conditions)



Copyright © 2012 SkyeTek, Inc.

SkyeTek®, Tagnostic®, SkyeWare™, Physical made Digital™, TagIQ™, ReaderDNA™, SkyeModule™ and AURA™ are trademarks or registered trademarks of SkyeTek, Inc. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice. ver. 080430

**SkyeTek Reader Technology** SkyeTek provides a variety of reader technology at both 13.56 MHz (HF) and 860- 960 MHz (UHF). ReaderDNA, a comprehensive reference design, is available for component level integration of the technology including complete design files, BOM, and test fixture. All SkyeTek readers leverage powerful firmware that drastically reduce hardware costs and are delivered in conjunction with ReaderDNA. SkyeModules are controlled via the SkyeTek Protocol, a powerful but simple communication protocol that grants the user access to all features of an RFID transponder. Further, they have been designed with flexible and modular embedded software that allows one to select only the features desired.



atlasRFIDstore.com  
1.888.238.1155 • Inside USA  
1.205.353.2244 • Outside USA

info@atlasRFIDstore.com • www.atlasRFIDstore.com