

2173 **BLUETOOTH®** LF, HF & NFC RFID READER

A MULTI-BAND, MULTI-ISO, PLATFORM-INDEPENDENT RFID READER



Made for
iPhone | iPad | iPod

Integrate RFID Into Your Solution!

The 2173 reader enables a compatible *Bluetooth®* host to read and write a wide variety of HF and LF RFID transponders as well as capture 1D and 2D barcodes (imager version only). These can be 'typed' into any application on the host device using the *Bluetooth®* HID keyboard mode. Alternatively, the reader can be commanded from an app on the host device. As the 2173 uses the existing TSL® ASCII 2 Protocol, developers can take advantage of the comprehensive, free SDKs provided by TSL® to develop in Xamarin, Java, Objective C or .NET.

Dual RFID Frequencies

The combined LF and HF RFID reader provides the ability to read and write to a wide variety of transponders at 125/134.2 kHz (LF) and 13.56 MHz (HF) including ISO 15693,ICODE (I & II), the complete Mifare family of ISO14443 (A&B) and the NFC standard ISO18092 ECMA-340.

Comprehensive Compatibility

Supported Manufacturer specific transponders include HID, NXP, EM Microelectronic, ATMEL and TI (Texas Instruments).

Features:

Multi-Band RFID Reading and Writing

Combined LF RFID, HF RFID and NFC reading and writing in an incredibly compact and lightweight device.

Multi-ISO RFID

Supports multiple ISO industry standards including ISO15693, ISO14443(A/B) and ISO18092 ECMA-340 (NFC).

Batch Data Collection

Removable high capacity Micro SD data card and real time clock for extended batch data collection with time stamp independent of the host connection.

OS Independence

The reader is compatible with Android, iOS and Windows.

High Performance Barcode Scanning

Integrated Motorola SE4500 imaging engine provides class leading barcode scan performance via its unique patent pending fast pulse illumination which delivers outstanding motion tolerance and class leading 1D and 2D data capture.

SPECIFICATIONS

Physical and Environmental Characteristics

Dimensions (LxWxH):	10.2 cm x 5.5 cm x 5.6 cm
Weight (inc battery):	157 g / 5.5 oz
User input:	Two Trigger buttons
User feedback:	Speaker, vibration motor, three LEDs
Power:	Removable, rechargeable 3.7 volt Lithium Polymer 1130 mAh battery pack, 4.2 watt hrs
Enclosure materials:	Polycarbonate

Performance Characteristics

Communication protocols:	TSL® ASCII 2.0 parameterised command set
Memory:	Supports up to 32 GB Micro SD/SDHC card
Compatible Host devices (Bluetooth®):	Any Bluetooth® Host ¹ supporting the Serial Port Profile (SPP) or Human Interface Device (HID) profile (Android, iOS, Linux, Mac, Windows). Comparison of Bluetooth® modes for TSL® UHF Readers.
Compatible Host devices (USB):	Any USB host with FTDI VCP driver support (Windows, Linux, Mac, Android)

Environmental

Operating Temp.:	-10°C to 40°C (14°F to 104°F)
Charging Temp.:	5°C to 40°C (41°F to 104°F)
Storage Temp.:	Less than 1 month at at -20 to +60°C (-4°F to 140°F) Less than 3 months at -20°C to +45°C (-4°F to 113°F) Less than 1 year at -20°C to +30°C (-4°F to 86°F)
Humidity:	5% to 85% non-condensing
Drop Spec:	Multiple drops to concrete: 4 ft./1.2 m ambient, 3ft / 0.9m across the operating temperature range
Tumble:	500 0.5 metre tumbles at room temperature (1,000 cycles)
Environmental Sealing:	IP54
Electrostatic Discharge (ESD):	± 15kVdc air discharge; ± 8kVdc contact discharge
MIL-STD 810F:	Meets and exceeds applicable MIL-STD 810F for drop, tumble and sealing
Construction:	RoHS compliant

RFID Performance

Frequency Range:	125/134.2 kHz (LF) / 13.56 MHz (HF)
Read Distance:	LF and HF: Up to 100 mm / 4" (dependent on transponder type).
RF Transmission Speed:	HF Air: up to 848 kbit/s
Standards supported:	ISO14443A, ISO14443B, ISO18092 ECMA-340 (NFC), ISO15693 plus many 125 kHz, 134.2 kHz standards.

Supported Tag-ICs :

ISO14443A:
LEGIC Advant¹⁾, MIFARE Classic 1k & 4k, MIFARE Classic 1k & 4k EV1²⁾, MIFARE Classic, MIFARE Classic EV1²⁾, MIFARE Mini, MIFARE DESFire EV1, MIFARE Plus S, X, MIFARE Pro X³⁾, MIFARE Smart MX³⁾, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Ultralight EV1, NTAG2xx, PayPass³⁾, SLE44R35, SLE66Rxx (my-d move)

ISO14443B:
Calypso³⁾, Calypso Innovatron protocol⁴⁾, CEPAS³⁾, Moneo³⁾, Pico Pass¹⁾, SRI4K, SRIX4K, SRI512, SRT512

ISO18092 ECMA-340:
NFC Forum Tag 1-5⁵⁾, NFC Peer-to-Peer, Sony FeliCa⁶⁾, NFC Active and passive communication mode

ISO15693:
EM4x33³⁾, EM4x35³⁾, HID iCLASS, ICODE SLI, LEGIC Advant¹⁾, M24LR16/64, SRF55Vxx (my-d vicinity)³⁾, Tag-it, PicoPass¹⁾

125 kHz, 134.2 kHz:
AWID, Cardax⁷⁾, CASI-RUSCO, Cotag, Deister, EM4100, 4102, 4200⁸⁾, EM4050, 4150, 4450, 4550, EM4305⁹⁾, FDX-B, HITAG 1¹⁰⁾, HITAG 2¹⁰⁾, HITAG S¹⁰⁾, Keri, Miro, Nedap⁷⁾, Pyramid, Q5, T5557, T5567, T5577, TIRIS/HDx, TITAN (EM4050), UNIQUE, ZODIAC⁹⁾

And also:
G-Prox⁷⁾, HID DuoProx II (1336), HID ISO Prox II (1386), HID Micro Prox (1391), HID ProxKey III (1346), HID Prox, HID Prox II (1326), Indala, ioProx, Nexwatch, HID iCLASS SE/SR/SEOS(CSN and Facility Code/PAC)¹¹⁾

¹⁾UID only ²⁾r/w enhanced security features on request ³⁾r/w in direct chip command mode ⁴⁾UID only, read/write on request ⁵⁾NFC Forum Tag 1 on request only ⁶⁾UID + r/w public area ⁷⁾Hash value only ⁸⁾Only emulation of 4100, 4102 ⁹⁾On request ¹⁰⁾Without crypto ¹¹⁾UID + PAC (CSN & Facility Code), r/w on request ¹²⁾ External interface required

Barcode Scanning

Imager:	Motorola SE4500 2D imager
Sensor Resolution:	752 x 480 pixels
Field of View:	Horizontal: 40°, Vertical: 25°
Focal Distance:	SR: 8 in. DL: 5.3 in. HD: 2.9 in.
Aiming LED (VLD):	655 ± 10 nm Laser
Illumination Element:	625 ± 5 nm LEDs (2x)
Min. Print Contrast:	Minimum 25%
Symbologies Supported:	1D: All major codes 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)

SPECIFICATIONS

Ranges ³ :	DL Focus	Near	Far
	5 mil Code 39	1.4 in./36 mm	7.3 in./185 mm
	100% UPC	1.6 in./41 mm	12 in./305 mm
	5 mil PDF417	2.8 in./71 mm	4.5 in./114 mm

Communication

Bluetooth®:	Bluetooth® Version 4.1
Bluetooth® Profiles:	SPP Profile HID Profile Apple iAP2 Bluetooth® Low Energy
Bluetooth® Power:	Class 2
Bluetooth® Range ⁴ :	30m
Bluetooth® Pairing:	Simple Secure Pairing, NFC OOB Pairing

Peripherals and Accessories

External interface:	MicroUSB connector for battery charging, and USB connectivity.
USB operating modes:	Tethered for real time data capture in conjunction with SmartWedge software. Download of stored scan data.
Optional external charger:	TSL® 1136 4-Slot Desktop Battery Charger

Regulatory

General:	TBA
Electrical Safety:	TBA
EMI/RFI:	TBA
Laser Safety:	TBA

¹ Compatible Bluetooth® stack required in the Host device

² Tag Read/Write performance is dependent on tag type, items tagged, number of tags in the field and other radio and environmental factors

³ Artificial lighting can affect scanning performance

⁴ Open field

Part Numbers

2173-BT-IMG	2173 Wearable Bluetooth® Barcode Scanner with 2D Imager, USB
2173-BT-LF-HF-A1	2173 Wearable Bluetooth® LF/HF RFID Reader without Imager
2173-BT-LF-HF-A1-PI	2173 Wearable Bluetooth® LF/HF RFID Reader, no Imager, PI Card (HID Prox and iCLASS) Reading
2173-BT-LF-HF-IMG	2173 Wearable Bluetooth® LF/HF RFID Reader with 2D Imager
2173-BT-LF-HF-IMG-PI	2173 Wearable Bluetooth® LF/HF RFID Reader, 2D Imager, PI Card (HID Prox and iCLASS) Reading

Warranty

The TSL 2173 reader is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

ABOUT TSL®

ABOUT



TSL® | Global Leaders in Mobile RFID

Technology Solutions UK Ltd (TSL®) is a leading manufacturer of high performance mobile RFID readers used to identify and track products, assets, data or personnel.

For over two decades, TSL® has delivered innovative data capture solutions to Fortune 500 companies around the world using a global network of distributors and system integrators. Specialist in-house teams design all aspects of the finished products and software ecosystems, including electronics, firmware, application development tools, RF design and injection mould tooling.

TSL® is an ISO 9001:2015 certified company.



ISO 9001: 2015

Copyright © 2019 Technology Solutions (UK) Ltd. All rights reserved. Technology Solutions (UK) Limited reserves the right to change its products, specifications and services at any time without notice.

1 (888) 238-1155 Inside USA • 1 (205) 383-2244 Outside USA
info@atlasRFIDstore.com • www.atlasRFIDstore.com

atlasRFIDstore.com