





## 2.09" x 2.09" TAGEOS EOS-340 M730 INLAY

The blank Vulcan RFID™ Label (2.09" x 2.09") - with Tageos EOS-340 M730 Inlay provides long read ranges regardless of label orientation, making them ideal for applications where placement of the label cannot be controlled or may vary, such logistics and retail. Manufactured ensure to optimum performance, these square 2.09" x 2.09" thermal transfer, smooth film labels standard with come the EOS-340 inlay and Impinj M730 integrated circuit. With a PET substrate rather than paper, this inlay exhibits a heightened durability allowing it to last longer.

The Vulcan RFID™ Label (2.09" x 2.09") - with Tageos EOS-340 M730 Inlay is great for a variety of applications including but not limited to:

- Inventory Visibility
- · Parts Management
- Supply Chain
- · Item Level Tagging





## **Specifications**

LECTRICAL

Operating Frequency:	Global (860-960 MHz)
Air Interface Protocol:	EPCglobal UHF Class 1 Gen 2 (ISO-18000-6C)
IC Type:	Impinj M730
Memory:	EPC 128 Bits, TID 96 Bits
EPC Memory Content:	Not Guaranteed Unique
Max Read Distance:	Testing Recommended
Applicable Surface Materials:	Wood, Plastic, Glass, Cardboard


CHANICAL

Tag Form Factor:	White Wet Label Tag, No Perforation
Tag Materials:	Printable White Film (Thermal Transfer)
Recommended Ribbon:	Wax Resin Ribbon
Attachment Method:	General Purpose Permanent Adhesive
Dimensions:	53 x 53 mm (2.09 x 2.09 in)
Weight:	1 g (0.002 lbs)
Core ID:	76.2 mm (3 in)
External Roll Diameter:	Up to 203.2 mm (8 in)
Quantity per Roll:	2,500 Labels
Pitch:	57.15 ± 1 mm (2.25 ± 0.04 in)

Operating Temperature:	-40° to +85°C (-40° to +185°F)



## Diagrams





## About Vulcan RFID™ Products

Vulcan RFID™ offers a broad range of innovative RFID readers, antennas, custom RFID tags, and accessories suited for a wide variety of industries and applications. Designed to deliver superior accuracy and reliability, Vulcan products RFID™ exceptional flexibility and performance. Vulcan RFID™ delivers an extensive product portfolio that includes both UHF and NFC products that support a large variety of market solutions. Manufactured to withstand environments ranging from mild to extreme, Vulcan RFID™ products enable end-users to reach and sustain high levels of performance in the UHF or NFC frequency bands.











Inside USA 1 (888) 238-1155

Outside USA 1 (205) 383-2244

info@atlasRFIDstore.com www.atlasRFIDstore.com