




# CARGO OUTDOOR

## Technical Specifications

- **RF protocol** EPC global Class 1 Gen 2
- **Frequency** 902-928 MHz (US); 865-868 MHz (EU)
- **IC type (chip)**<sup>1</sup> Impinj M750
- **Chip memory**<sup>2</sup> 96 bits EPC; 96 bits TID; 32 bits user memory
- **Read range on metal**<sup>3</sup> Up to 39.37 ft (12 m)
- **Read range off metal**<sup>3</sup> Up to 19.69 ft (6 m)
- **Polarization** Linear
- **Radiation pattern on metal**



## Key Features

- + **12 m read range:** read from a distance
- + **Multi-surface:** for on/off metal asset
- + **Metal inserts:** rugged
- + **Various mounting systems**
- + **IP68 rating:** waterproof

## Applications

- RTI inventory
- Transportation and logistics
- Yard management
- Construction tools

## Environmental Specifications

### Temperatures



- Operational -40°C to +85°C
- Survival -40°C to +85°C (48 hours)

- **IP rating** IP68
- **Compression strength** 29 psi (200 kPa)
- **Shock** 3ft (1 m) to concrete/granite
- **Vibration** MIL-STD-810G
- **Warranty** 1 year

<sup>1</sup> The chip data retention is up to 50 years, based on chip operating under general environment conditions.


<sup>2</sup> EPC can be re-programmed, password protected, or permanently locked. TID is locked and unique at the point of manufacturing.

<sup>3</sup> Fixed reader



## Physical Specifications

- **Material** Industry grade polymer, Stainless steel
- **Dimensions (in)**<sup>1</sup> 3.94 x 1.02 x 0.30
- **Dimensions (mm)**<sup>1</sup> 100 x 26 x 8.90
- **Rivet hole diameter**<sup>2</sup> 0.14 in (3.50 mm)
- **Weight** 0.62 oz (17.80 g)




## Mounting Systems

- Pop rivets
- Screws
- Cable and zip ties
- Industrial adhesives (optional)

## Installation Instructions

1. Use M4 rivets for attachment:
  - Drill two holes (∅ 4) in the metal surface, pitch: 88.50 mm.
  - Utilize M4 rivets in conjunction with a rivet gun to securely fasten the tag onto the metal surface.
2. Use M4 screws for attachment:
  - Drill two holes (∅ 3.20) in the metal surface, pitch: 88.50 mm.
  - Perform a M4 thread tapping procedure.
  - Utilize M4 screws to securely attach the tag to the metal surface.



<sup>1</sup> Tolerance: +/- 0.02; +/- 0.50  
<sup>2</sup> Tolerance: +/- 0.008; +/- 0.200

## Industry Compliance



## Order Information

Cargo OUTDOOR US: X03A3-US100-M750

Cargo OUTDOOR EU: X03A3-EU100-M750

## Customization Options

- Encoding
- Laser Marking
- ATEX Certified Version

- Printing
- Industrial Adhesives

The information provided by Xerapy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet.

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.

