



**ZEBRA**

# 8000T Void Gloss

## FEATURES

- Thermal transfer, gloss label with a tamper-proof adhesive that leaves a VOID pattern when label is removed
- Some smear/scratch resistance
- Excellent durability and chemical resistance
- Available in white (05394RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White gloss polyester	2.0 mil
Adhesive	Permanent, tamper-evident acrylic-based	0.8 mil
Liner	50 lb. semi-bleached, kraft stock	3.2 mil
<b>TOTAL ± 10%</b>		<b>6.0 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
23° F (-5° C)	-20° F to 212° F (-29° C to 100° C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Up to 1 year

## CHEMICAL RESISTANCE

Chemical		Suggested Ribbon	
		6200	5095
Weak	Blood	●	●
	Body Fluid	●	●
	Salt Water	●	●
	Water	●	●
	Window Cleaner	●	●
Moderate	Alcohol	●	●
	Ammonia	●	●
	Bleach	●	●
	IPA	●	●
Harsh	Gasoline	●	●
	Grease	●	●
	Oil	●	●
Extreme	Acetone	NR	NR
	IR Reflow	NR	NR
	MEK	NR	NR
	TCE	NR	NR
	Xylene	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Tamper evident security labels



- Product identification



## 70C Void Performance on Stainless Steel

Dwell Time	% Voiding	% Adhesive Transfer
24 hours at RT	100%	95%

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.



atlasRFIDstore  
(205) 383-2244  
sales@atlasRFIDstore.com  
www.atlasRFIDstore.com

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.