



ZEBRA

PolyPro 3000T Gloss Removable

FEATURES

- Thermal transfer, polypropylene label
- Recommended for labeling applications requiring clean removability
- Available in white (10030763RM)
- May be used in desktop printers
- For best performance use 5095 ribbon

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White topcoated polypropylene film	3.6 mil
Liner	50 lb. kraft stock	3.2 mil
Adhesive	Removable acrylic	.6 mil
TOTAL ± 10%		8.5 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
32° F (0° C)	-40° F to 180° F (-40° C to 82° C)	72° F (22° C) at 50% RH

Expected Exterior Life
Up to 1 year

CHEMICAL RESISTANCE

Suggested Ribbon		
	Chemical	5095
Weak	Blood	●
	Body Fluid	●
	Salt Water	●
	Water	●
	Window Cleaner	●
Moderate	Alcohol	●
	Ammonia	●
	Bleach	●
	IPA	●
Harsh	Gasoline	●
	Grease	●
	Oil	●
Extreme	Acetone	●
	IR Reflow	●
	MEK	●
	TCE	●
	Xylene	●

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Temporary parking identification



- Window labeling



- Work in process labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.



atlasRFIDstore

(205) 383-2244

sales@atlasRFIDstore.com

www.atlasRFIDstore.com