

ZEBRA

SUGGESTED

APPLICATIONS

Shelf labeling

PolyPro 4000T Removable


FEATURES

- Thermal transfer, matte Kimdura polypropylene label with a removable acrylic adhesive
- · Good smear/scratch resistance
- · Excellent chemical resistance
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (05032RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White matte topcoated polypropylene	3.8 mil
Adhesive	Removable, acrylic- based	1.0 mil
Liner	50 lb. semi-bleached, kraft stock	3.2 mil
	TOTAL ± 10%	8.0 mil

ADHESIVE STRENGTH



TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
45°F	0°F to 160°F	72° F (22° C)
(7°C)	(-18°C to 71°C)	at 50% RH

Expected Exterior Life

2 years

CHEMICAL RESISTANCE

		Suggested Ribbon	
	Chemical	6100	3200
Weak	Blood	•	•
	Body Fluid	•	•
	Salt Water	•	•
	Water	•	•
	Window Cleaner	•	•
Moderate	Alcohol	•	•
	Ammonia	•	•
	Bleach	•	•
	IPA	•	•
Harsh	Gasoline		
	Grease		
	Oil		
Extreme	Acetone	•	•
	IR Reflow		
	MEK	•	•
	TCE	•	•
	Xylene	•	•

Recommended
Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.



Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.