# Afri.

### ZEBRA

## **Z-Band® Fun Wristbands**

#### **FEATURES**

- Direct thermal white polypropylene wristband with a permanent rubber adhesive tab for quick initial tack and permanent securement.
- Seven color options for color coding. The wristbands are available in red, yellow, blue, green, pink, orange, and purple.
- · Tamper-evident slits for security purposes.
- Meets common 1-day recreation wristbanding requirements with limited water exposure.
- Waterproof, and resistant to smearing, abrasion, sun lotions and creams, and hand sanitizers such as Purell®.
- Printed information is legible and scannable for 1 day.

#### **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	Direct thermal polypropylene	4.0 mil
	TOTAL ± 10%	4.0 mil

#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions	
40° F	-65° F to 160° F (-54° C to 71° C)	72° F (22° C) at 50% RH	

#### **Expected Exterior Life**

1 day

#### **CHEMICAL RESISTANCE**

	Chemical	Direct Thermal
Weak	Blood	•
	Body Fluid	•
	Salt Water	•
	Water	•
	Window Cleaner	•
O)	Alcohol	•
erat	Ammonia	•
Moderate	Bleach	•
	IPA	•
_	Gasoline	NR
Harsh	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

Recommended ○ Test in Your Application NR Not Recommended

## Recommended Darkness and Print Speed Settings:

- Wristband Cartridge Printers -- Print speed and darkness setting are automatically set by the cartridge
- ZPL Printers: Darkness: 12 Print Speed: 2ips
- EPL Printers: Darkness: 12 Print Speed: 2ips

SUGGESTED APPLICATIONS

Ticketing



 Theme park entertainment -Access rights



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.



**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.