



ZEBRA

Z-Perform 1000T Tag

FEATURES

- Thermal transfer, smooth, uncoated paper tag
- Recommended for printing applications up to 4 inches per second
- Available in 7.5mil (05168RM) and 9.5mil thickness (05242RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth uncoated thermal transfer paper	7.5 / 9.5 mil
TOTAL ± 10%		7.5 / 9.5 mil

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-50°F to 200°F (-46°C to 93°C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

Chemical		Suggested Ribbon		
		6000	2000	6100
Weak	Blood	●	●	●
	Body Fluid	●	●	●
	Salt Water	●	●	●
	Water	●	●	●
	Window Cleaner	●	●	●
Moderate	Alcohol	NR	NR	NR
	Ammonia	NR	NR	NR
	Bleach	NR	NR	NR
	IPA	NR	NR	NR
Harsh	Gasoline	NR	NR	NR
	Grease	NR	NR	NR
	Oil	NR	NR	NR
Extreme	Acetone	NR	NR	NR
	IR Reflow	NR	NR	NR
	MEK	NR	NR	NR
	TCE	NR	NR	NR
	Xylene	NR	NR	NR

● Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

- Retail hang tags



- General purpose ticketing



- Work in process tagging



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



atlasRFIDstore

(205) 383-2244

sales@atlasRFIDstore.com

www.atlasRFIDstore.com