



ZEBRA

Zebra ZBR2000 Inlay

DETAILS

- General Purpose inlay
- Economical choice for 4" wide labeling applications
- Applications: Case / Pallet, Asset tracking
- Meets Auburn ARC Specs:
A, B, C, D, F, G, I, K, L, M, N, Q



THEORETICAL ** READ RANGES ON VARIOUS SURFACES (m)

Material	ETSI (865-868 MHz)	FCC (902-928 MHz)
Air	16	17
Cardboard	15	12
Fiberglass	10	12
Glass	9	15
PTFE	15	11
Polyacetyl	11	11
PVC	11	11
Rubber	10	12

SUGGESTED APPLICATIONS

- Case/pallet labeling




- Transportation & Logistics



TECHNICAL INFORMATION

- Chip: NXP UCODE 8
 - EPC memory: 128 bit
 - User memory: N/A
 - TID: 96 bit factory locked (48 bit unique)
 - Read Sensitivity: -23dBm
 - Write Sensitivity: -18dBm
 - EPC Gen2v2
- Extreme high sensitivity chip with read ranges up to 17m in free space

RADIATION PATTERN*



* Read range drops to 6% of maximum when inlay is perpendicular (90° and 270°) to the reading antenna.

**Theoretical read range data is meant to be directional. Actual performance will depend on your application and environment. Testing is recommended.

All inlays certified by Zebra have been pre-tested with Zebra printers and readers. For more information on Auburn's ARC specifications, testing, and the certification process, please go to rfid.auburn.edu.



Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2016 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



atlasRFIDstore
(205) 383-2244
sales@atlasRFIDstore.com
www.atlasRFIDstore.com