

INVENGO XC-AF12 HIGH PERFORMANCE





About Invengo's XC-AF12 High Performance Antenna

Invengo XC-AF12 antenna offers high gain, ruggedness and excellent shock and vibration resistance in a unique design. The XC-AF12 circular polarized antenna is ideal for transportation, logistics, warehousing and asset tracking applications.



Invengo – the global RFID technology provider – is a leading developer and manufacturer of high quality, intelligent RAIN RFID (UHF) and NFC (HF) inlays, tags and connectivity solutions utilized in the Internet of Things (IoT). With a focus on RFID innovation, Invengo has created a leading product line in retail, library, pharmaceutical, healthcare, (public) transportation and many other industries.


Invengo Technology Pte. Ltd. (SG) is the International Headquarters of Invengo Information Technology Co. Ltd, listed on Shenzhen Stock Exchange (SZSE: 002161.SZ). Employing over 500 people globally, Invengo is one of the largest publicly traded, RFID oriented companies in the world.

Features


- Operating Frequency
 840 ~ 868 MHz and 902 ~ 928 MHz
- High Gain
- Circular Polarization
- Low VSWR
- Protection Level: IP65
- Durable and clean design
- Simple installation and maintenance




Radiation Pattern




E Phase



Mounting Bracket





Product Specifications

Per	forma	ance	Paramet	er	

Operating Frequency	840 ~ 868 Mhz
	902 ~ 928 MHz

VSWR ≤ 1.3:1
Gain 7.15 dBi
H-Plane HPBW 60° E-Plane HPBW 60° Polarization Circular

Antenna Impedance
Environmental

Operating Temperature -40°C to 70°C (-40°F to 158°F) Storage Temperature -40°C to 70°C (-40°F to 158°F)

 50Ω

Humidity Range 5% ~ 95% RH

Protection Level IP65

Physical Parameters

Dimensions 291 x 291 x 52 mm


11.5 x 11.5 x 2 in

Weight Approx. 0,91 kg / 2.0 Lbs

Case Material Plastic ASA, Aluminium

Models

ID XC-AF12



* atlasRFIDstore.com 1.888.238.1155 • Inside USA 1.205.383.2244 • Outside USA

info@atlasRFIDstore.com • www.atlasRFIDstore.com