


WEB

Optimized size and shape for apparel applications.



Web tags and inlays are designed for the unique identification of items such as apparel and electronics. They are suitable especially for item-level retail, logistics and supply chain applications.

Web products are compact and ideally shaped inlays for apparel hang tags providing high read reliability with low total applied costs.

Web inlays with NXP U-Code G2iL IC are approved and certified in the University of Parma's RFID Lab tests, where the Web inlays have proven their excellent performance.

Benefits:

- ▶ High end product for item-level tagging in apparel and electronics.
- ▶ Ideal size and shape for apparel hang tags, compact and reliable.
- ▶ Perfect for low cost hang tags and care labels.
- ▶ Excellent performance even when stacked in close proximity.
- ▶ ISO 9001:2008 Quality Management System and ISO 14001:2004 Environment Management System support.
- ▶ Unique TID.

Overview

Operating Frequency

860 - 960 MHz

Integrated Circuit (IC)

NXP U-Code G2iL

Antenna Size

30 x 49 mm (1.18 x 1.93 in)

Die-cut Size

34 x 54 mm (1.34 x 2.13 in)

International Standards

EPC Class 1 Gen 2

ISO 18000-6C

Quality Assurance



100% performance tested

Application Areas

- ▶ Apparel
- ▶ Brand Protection
- ▶ Supply Chain Management

Technical Features	
IC	NXP U-Code G2iL
Memory	EPC memory 128 bit
Frequency	860-960 MHz
Antenna Size	30 x 49 mm / 1.18 x 1.93"
Die-cut Size	34 x 54 mm / 1.34 x 2.13"
Web Width	40 mm / 1.58"
Operating Temperature	-40°C to 85°C / -40°F to 185°F
Bending Diameter (D)	> 50 mm, tension max. 10 N
Delivery Formats	Dry inlay, wet inlay, tag
Adhesive	Acrylic, water borne adhesive
Adhesive Usage Temperature	min. -20°C to 80°C / min. -4°F to 176°F
Qty/Reel	5,000 dry inlays per reel, 2,000 wet inlays or tags per reel
Core Size	76 mm / 3"
Shelf Life: minimum of 2 years from the date of manufacture in	20°C / 68°F, 50% RH

SMARTRAC TECHNOLOGY GROUP uses three different qualification methods to evaluate the quality and reliability of RFID inlay and tag products. Products are tested according to IEC 60068-2-67 (temperature and humidity), JESD22-A104-B (temperature cycling) and an in-house developed bending test.



All the graphs are indicative: performance in real life applications may vary. The data has been determined based on calculations for transmitters with a 2W ERP output power level.



RoHS 



atlasRFIDstore.com
1.888.238.1155 • Inside USA
1.205.383.2244 • Outside USA

info@atlasRFIDstore.com • www.atlasRFIDstore.com